Republic of the Philippines

DEPARTMENT OF SOCIAL WELFARE AND DEVELOPMENT

Cordillera Administrative Region

40 North Drive Baguio City

		REQUEST FOR QUOTATION (RFQ)
PR/PP No.: End- user:	2025-04-373	RFQ No.: 2025-04-400
	ICTS of Project:	ABC: ₱186,000.00
	Purchase	and Delivery of CCTV Hardware for SWAD Abra Mode of Procurement: SMALL VALUE PROCUREMENT
Sir/Ma	Please quote your lowest price on the it t to the Terms and Condition provided in this	tem/s described below inclusive of taxes duly signed by you or your authorized representative, RFQ and submit personally to the Office of the Procurement Section, 40 North Prive, Baguio City

MAY NS

GASCON, JR

TERMS AND CONDITIONS:

Quotations in excess of the ABC will be REJECTED.

or through email at bacsec.car@dswd.gov.ph on or before __

- 2. For total quoted price , quotations with a dash or zero shall be deemed free of charge.
- 3. All entries must be typewritten/printed/onghand. Any erasure in the quotation must be countersigned by the bidder/ representative,
- otherwise quotation will be rejected. 4. The Procuring Entity may give due preference to goods being offered with green component.
- 5. If necessary, the BAC through the TWG, may require an occular inspection of the venue/place of business/goods being offered.
- 6. Delivery of Goods / Services is as indicated in the next page.
- 7. Price validity shall be for a period of 120 calendar days from RFQ Opening of the BAC until confirmation of Purchase Order by the winning supplier.
- 8. The following documents shall be attached upon submission of quotation, otherwise your quotation will not be accepted, please disregard if already submitted:
- Updated Mayor's / Business Permit
- b. PhilGEPS Registration Certificate or PhilGEPS Registration Number to be indicated in space below (except for Negotiated Procurement - Emergency Cases, Sec. 53.2, RA 9184 IRR)
- o Income/Business Tax Return (for Small Value Procurement, Direct Contracting above P500K, Emergency Cases above P500K, and Lease of Real Property/Venue).
 - o Official Receipt or Invoice issued by BIR (as applicable, a mere picture of the receipt or invoice can suffice)
- 9. Where there is discrepancy between: (a) total price per item and unit price for the item as extended or multiplied by the quantity of that item, the unit price shall prevail; (b) stated total price and the actual sum of prices of component items, the lower shall prevail; (c) unit cost in the detailed estimate and unit cost in the bill of quantities, the latter shall prevail.
- 10. Suppliers/Contractors who refuse to accept correction of price offer after Bid Evaluation shall be disqualified.
- 11. Award of Contract shall be made to the Lowest Calculated Responsive Quotation (LCRQ) that complies to the technical specifications and the terms and conditions stated herein
- 12. The BAC shall require the bidder with Lowest Calculated Responsive Quotation (LCRQ) to submit the Omnibus Sworn Statement prior to issuance of Award / Purchase Order with ABC amounting to P500,000.00 for Emergency Cases and P50,000.00 above for Small Value Procurement.
- 13. Upon approval of the Purchase Order (PO), the Procurement Section may send or forward the approved PO for confirmation to the winning bidder. The approved PO shall be confirmed within three (3) calendar days upon sending the approved PO to the winning bidder's officially registered email address or upon notification of the winning bidder that the approved Purchase Order is available for confirmation. Failure to submit the confirmed PO within the 3-day period may cause the automatic cancellation of the PO.
- 14. If the Supplier fails to deliver the required goods /services as specified in the Award / Purchase Order, the Procuring Entity may disqualify bidder from participating future procurement activities to be conducted by DSWD-CAR.
- 15. Liquidated damages equivalent to one tenth of one percent (0.001) of the value of the goods not delivered within the prescribed delivery period may be imposed per day of delay. The Procuring Entity (PE) may rescind the contract once the cumulative amount of liquidated damages reaches ten percent (10%) of the amount of the contract, without prejudice to other courses of action and remedies open to it.
- 16. Further information may be obtained from the Procurement Section with telephone number (074) 661-0430 local 25123, 0969-572-9176 or email address bacsec.car@dswd.gov.ph.

Republic of the Philippines

DEPARTMENT OF SOCIAL WELFARE AND DEVELOPMENT Cordillers Administrative Region

TITIAN DO. POLITAINED DESCRIPTION SET SET SET SET SET SET SET SE		,	Cordillera Administrative	Region				
TITION NO. Procedure of COTY MARDWARE SHOULD CONTAIN THE FOLLOWING PERPHERALS: They De unite fluidle Processes Specifications: It least Full 101 1039 Dr. Cameras Specific			40 North Drive, Baguin	ION (RFQ)				
DECEMBER OF DECEMBER OF STATE	Accordance		REQUESTION QUESTION		UNIT	UNIT PRICE	TOTAL	
GCTV HARDWARE SHOULD CONTAIN THE FOLLOWING PRIPHERALS: Two Cig Justies Builate IP Camerae Specifications: It least Fail City 1-85 Me Veloco compression Verificate Lans or Author Occus, Capable of operating in born normal and poorly its environment Westmerproof, as least IPF5 housing Westmerproof, as least IPF5 housing Westmerproof, as least IPF5 housing Accepts Polt, 1-12 OC Power, or extended Polt Westmerproof, 1-12 Me Vinderows Software, or Morbies Applications Accepts Polt, 1-12 OC Power, or extended Polt Westmerproof, 1-12 Me Vinderows Software, or Morbies Applications Accepts Polt, 1-12 OC Power, or extended Polt Westmerproof, 1-12 Me Vinderows Software, or Morbies Applications Accepts Polt, 1-12 OC Power, or extended Polt Westmerproof, 1-12 Me Vinderows Software, or Morbies Applications Accepts Polt, 1-12 OC Power, or extended Polt Westmerproof, 1-12 Me Vinderows Cheestion of Land Concepts Applications Accepts Polt, 1-12 OC Power, or extended Polt Westmerproof, 1-12 Me Vinderows Cheestion of Land Concepts Westmerproof, 1-12 Me Vinderows Cheestion Westmerproof, 1-12 Me Vinderows Cheesting Westmerproof, 1-12 Me Vin	TEM NO.			Q.				_
GCTV HARDWARE SHOULD CONTAIN THE FOLLOWING PRIPHERALS: Two Cig Justies Builate IP Camerae Specifications: It least Fail City 1-85 Me Veloco compression Verificate Lans or Author Occus, Capable of operating in born normal and poorly its environment Westmerproof, as least IPF5 housing Westmerproof, as least IPF5 housing Westmerproof, as least IPF5 housing Accepts Polt, 1-12 OC Power, or extended Polt Westmerproof, 1-12 Me Vinderows Software, or Morbies Applications Accepts Polt, 1-12 OC Power, or extended Polt Westmerproof, 1-12 Me Vinderows Software, or Morbies Applications Accepts Polt, 1-12 OC Power, or extended Polt Westmerproof, 1-12 Me Vinderows Software, or Morbies Applications Accepts Polt, 1-12 OC Power, or extended Polt Westmerproof, 1-12 Me Vinderows Software, or Morbies Applications Accepts Polt, 1-12 OC Power, or extended Polt Westmerproof, 1-12 Me Vinderows Cheestion of Land Concepts Applications Accepts Polt, 1-12 OC Power, or extended Polt Westmerproof, 1-12 Me Vinderows Cheestion of Land Concepts Westmerproof, 1-12 Me Vinderows Cheestion Westmerproof, 1-12 Me Vinderows Cheesting Westmerproof, 1-12 Me Vin		Purchase and Delivery of CCTV Hardware for SV	VAD Abra	-	SET			
SHOULD CONTAIN THE FOLLOWING PRIPHERALS: Two (2) usils Builder IP Camera Specifications: It least Full HO 1008 Charless stage and the Control of the Camera Supports Line Full HO 1008 Charless Accepts Pole 1 170 Charless Specifications: In least Full HO 1008 IP Camera Specifications: In least Full HO 1008 IP C	4			1	SET			
Specifications: at least Pull HO 1001 P Cameras aupports HASH-N, HASS Vision compression varificat Leris or Acade focus, Cupalities of operating in both normal and poorly its varificate Leris or Acade focus, Cupalities of operating in both normal and poorly its varificate Leris or Acade focus, Cupalities of Operating in Both normal and poorly its varificate Leris or Acade focus, Cupalities of Compression Advanced Analytics intrusion Desentions Software, or Moole Applications (Vastelly well and the Compression Compression Software, or Moole Applications (Vastelly well HO 1001 IP Camera Sit (Similar Direct Leris Compression) supports H.289+, Kalls Video compression supports H.289+, Kalls Video compression varifications: at least Field HO 1001 IP Camera supports H.289+, Kalls Video compression Weatherproof, at least IP86 Roussing Advanced Analytics: Instrusion Cultimos Software, or Welle Applications Acazepts Field, 12/0 CP Power, or extended Poil Warranty: 1 year One (1 unit Network Video Recorders Specifications: 15-CH (NYR) that support all CCTV cameras and with 1 units Surveillance Hard Drive 1730 Warranty: 1 year One (1) unit Network Video Recorders Specifications: 15-CH (NYR) byta support all CCTV cameras and with 2 units Surveillance Hard Drive 1730 Warranty: 1 year One (1) unit Network Router Specifications: On								
Specifications: al least Yul 258, 1, 124, 500 per Compression Varifocal Lams or Auto-Focus, Capable of operating in bow normal and poorly lit environment Veratherproof, all tass (PST housing) Accepts PoE, 12V DC Power, or extended PoE Verathery; 1 year Six (8) units Dome IP Camera Specifications: all tass Full HO (PST housing) Accepts PoE, 12V DC Power, or extended PoE Verathery; 1 year Six (9) units Dome IP Camera supports Lams or Auto-Goucis, capable of operating in both normal and poorly lit environment Veratherproof, all tass (PSE) bousing Advanced, Multi-Capable of poperating in both normal and poorly lit environment Veratherproof, all tass (PSE) bousing Advanced, Multi-Capable of poperating in both normal and poorly lit environment Veratherproof, all tass (PSE) bousing Advanced, Multi-Capable of poperating in both normal and poorly lit environment Veratherproof, all tass (PSE) bousing Advanced, Multi-Capable of poperating in both normal and poorly lit environment Veratherproof, all tass (PSE) bousing Advanced, Multi-Capable of poperating in both normal and poorly lit environment Veratherproof, all tass (PSE) bousing Advanced, Multi-Capable of poperating in both normal and poorly lit environment Veratherproof, all tass (PSE) bousing Advanced, Multi-Capable of poperating in both normal and poorly lit environment Veratherproof, all tass (PSE) bousing One (1) unit Network (Viron poerating and with Early lite (PSE) All tass (PSE) bousing Veratherproof, all tass (PSE) bousing Veratherproof, all tass (PSE) Veratherproof, all tass (SHOULD CONTAIN THE FOLLOWING FERNING						
Specifications: al least Yul 258, 1, 124, 500 per Compression Varifocal Lams or Auto-Focus, Capable of operating in bow normal and poorly lit environment Veratherproof, all tass (PST housing) Accepts PoE, 12V DC Power, or extended PoE Verathery; 1 year Six (8) units Dome IP Camera Specifications: all tass Full HO (PST housing) Accepts PoE, 12V DC Power, or extended PoE Verathery; 1 year Six (9) units Dome IP Camera supports Lams or Auto-Goucis, capable of operating in both normal and poorly lit environment Veratherproof, all tass (PSE) bousing Advanced, Multi-Capable of poperating in both normal and poorly lit environment Veratherproof, all tass (PSE) bousing Advanced, Multi-Capable of poperating in both normal and poorly lit environment Veratherproof, all tass (PSE) bousing Advanced, Multi-Capable of poperating in both normal and poorly lit environment Veratherproof, all tass (PSE) bousing Advanced, Multi-Capable of poperating in both normal and poorly lit environment Veratherproof, all tass (PSE) bousing Advanced, Multi-Capable of poperating in both normal and poorly lit environment Veratherproof, all tass (PSE) bousing Advanced, Multi-Capable of poperating in both normal and poorly lit environment Veratherproof, all tass (PSE) bousing Advanced, Multi-Capable of poperating in both normal and poorly lit environment Veratherproof, all tass (PSE) bousing One (1) unit Network (Viron poerating and with Early lite (PSE) All tass (PSE) bousing Veratherproof, all tass (PSE) bousing Veratherproof, all tass (PSE) Veratherproof, all tass (Two (2) units Bullet IP Camera						
supports H.286+, 1285 video Compression Variotecal Lesser of Auth-Once, Capsable of operating in both normal and poorty it Worthursproof, at least IPS7 housing Advanced Analytics: Intrusion Detection (Line Crossing) Execution Useable with NVR recorder, PC Windows Applications Accepts Poet, 12 VD C Pewer, or sealershed PoE Warrardy; 1 year Six (6) units Borne IP Camera Specifications: at least 12 (186) per Camera specifications: at least 12 (186) per Camera specifications: at least 12 (186) per Camera Warrardy; 19 per position of the Camera Accepts Poet, 12 VD C Power, or estanded PoE Warrardy; 19 per position of the Camera and with 2 units Surveillance Hard Drive 17 per position of the Camera and Warrardy; 19 per position of the Camera and with 2 units Surveillance Hard Drive 17 per position of the Camera and Warrardy; 19 per position of the Camera and with 2 units Surveillance Hard Drive 17 per position of the Warrardy; 19 per position of the Camera and with 2 units Surveillance Hard Drive 17 per position of the Camera and Warrardy; 19 per position of the Camera and Warrardy; 19 per position of the Camera and Camer		Specifications:		\				
Varifocal Lens or Auto-Rockit, Capables to systems or systems or systems or systems of the control of the contr		supports H.265+, H.265 video compression	normal and poorly lit					
Weatherproof, at least IRPT Incusing Advanced Analytics: Intracts Ondowns Software, or Mobile Applications Usether with Carlo Control P Camera Bereath Carlo Ca		Varifocal Lens or Auto-focus, Capable of operating in a		1				
Advanced Analytics: infrusion Discriptions Software, or Mobile Applications Accepts Ped. 179 DC Rower, or extended PoE Accepts Ped. 170 DC Rower, or extended PoE Warranty; 1 year Six (8) units Dome IP Camera specifications: 1 steast Fill 1854 + 1.285 video compression Varificated Lines or Auth-Genue. Capable of operating in beh normal and poorly lit environment Vestatroproof, at least IPRS Rousing Advanced Analy Recorder, PC Windows Software, or Mipblie Applications Accepts PoEL 170 DC Power, or estanded PoE Warranth; 1 year One (1) unit Network Video Recorders Should have an integrated Systemityapilication for CCTV operations such as but not limited for eachimetire view, video recording, remote search, playback, backup, etc. Illimited for eachimetire view, video recording, remote search, playback, beckup, etc. Illimited for eachimetire view, video recording, remote search, playback, beckup, etc. Illimited for eachimetire view, video recording, remote search, playback, beckup, etc. Illimited for eachimetire view, video recording, remote search, playback, beckup, etc. Illimited for eachimetire view, video recording, remote search, playback, beckup, etc. Illimited for eachimetire view, video recording, remote search, playback, beckup, etc. Illimited for eachimetire view, video recording, remote search, playback, beckup, etc. Illimited for eachimetire view, video recording, remote search, playback, beckup, etc. Illimited for eachimetire view, video recording, remote search, playback, beckup, etc. Illimited for eachimetire view, video recording, remote search, playback, beckup, etc. Illimited for eachimetire view, video recording, remote search, playback, beckup, etc. Illimited for eachimetire view, video recording, remote search, playback, beckup, etc. Illimited for eachimetire view, video recording, remote search, playback, beckup, etc. Illimited for eachimetire view, video recording, remote search, playback Verarray; view One (1) unit Bower Burge Portoscor Illimited for eachimetire view, video remote view, etc			etection					
Accepts Picf. 17 U. U. Power, to Accepts Picf. 17 U. U. Power, to Accepts Picf. 17 U. U. Power, to Accept Picf. 17 U. Power, to Acce		Advanced Analytics: Intrusion Detection / Line Crossing	le Applications					
Six (g) units Dome IP Camera Specifications: at lease Full HO 1980 IP Camera supports H.386+, H.286 video compression variocal Lens or Aut-focus. Capable of operating in both normal and poorly lit environment and lens of Auth-focus. Capable of operating in both normal and poorly lit environment and lens of Auth-focus. Capable of operating in both normal and poorly lit environment and lens of Auth-focus and lens of the Company of Authority of the Company of Authority of		Accepts PoE, 12V DC Power, or extended PoE						
at least Pull HD 1030 IP Cameras supports H.256+, M.258 Wide compression supports H.256+, M.258 Wide compression property H.256+, M.258 Wide compression washerproof, at least IPS6 housing Advanced Analytics: Intrusion Detection / Line Crossing Defection Usable with NWR recorder, PC Windows Software, or Mabile Applications Accepts Poet, 1720 Powers, or etanded Post Warranty: 1 year One (1) until Network Video Recorders Specifications: 15-CH (NWR) that support all CCTV cameras and with 2 behts Surveillance Hard Drive eTB Should have an integrated System/Application for CoTW operations such as but not limited to residential with the Windows Application for CoTW operations and the search, playback, backup, etc. Tamper H.256+A.264/MPEG4 video formatise. Support Tallyaback Warranty: 1 year One (1) unit PoE Network Switch Specifications: 16 Glapbil PoE ports Power budget 230W Warranty: 1 year One (1) unit Retwork Router Specifications: Se Glapbil Ethernet, Dual Core 850MHz, 264MB RAM, USB, micro SD (optional) Warranty: 1 year One (1) unit Surveillance Smart TV Monitor Specifications: Display bye and size: at least 44 C3" UHD Direct-lit LED with HDR10 standard Retwork the whole Not Specifications: Display they and size: at least 44 C3" UHD Direct-lit LED with HDR10 standard Retwork the whole Not Specifications: Display they and size: at least 44 C3" UHD Direct-lit LED with HDR10 standard Retwork the whole Not Specifications: Display to and size: at least 44 C3" UHD Direct-lit LED with HDR10 standard Retwork the whole Not Specifications: Display to and size: at least 44 C3" UHD Direct-lit LED with HDR10 standard Retwork the whole Not Specifications: Display to and size: at least 44 C3" UHD Direct-lit LED with HDR10 standard Retwork the whole Not Specifications: Display to and size: at least 44 C3" UHD Direct-lit LED with HDR10 standard Retwork the whole Not Specifications: Display to and size: at least 44 C3" UHD Direct-lit LED with HDR10 standard Retwork the standard frame/view per device should find find find should b		Warranty: 1 year						
at least Pull HD 1030 IP Cameras supports H.256+, M.258 Wide compression supports H.256+, M.258 Wide compression property H.256+, M.258 Wide compression washerproof, at least IPS6 housing Advanced Analytics: Intrusion Detection / Line Crossing Defection Usable with NWR recorder, PC Windows Software, or Mabile Applications Accepts Poet, 1720 Powers, or etanded Post Warranty: 1 year One (1) until Network Video Recorders Specifications: 15-CH (NWR) that support all CCTV cameras and with 2 behts Surveillance Hard Drive eTB Should have an integrated System/Application for CoTW operations such as but not limited to residential with the Windows Application for CoTW operations and the search, playback, backup, etc. Tamper H.256+A.264/MPEG4 video formatise. Support Tallyaback Warranty: 1 year One (1) unit PoE Network Switch Specifications: 16 Glapbil PoE ports Power budget 230W Warranty: 1 year One (1) unit Retwork Router Specifications: Se Glapbil Ethernet, Dual Core 850MHz, 264MB RAM, USB, micro SD (optional) Warranty: 1 year One (1) unit Surveillance Smart TV Monitor Specifications: Display bye and size: at least 44 C3" UHD Direct-lit LED with HDR10 standard Retwork the whole Not Specifications: Display they and size: at least 44 C3" UHD Direct-lit LED with HDR10 standard Retwork the whole Not Specifications: Display they and size: at least 44 C3" UHD Direct-lit LED with HDR10 standard Retwork the whole Not Specifications: Display to and size: at least 44 C3" UHD Direct-lit LED with HDR10 standard Retwork the whole Not Specifications: Display to and size: at least 44 C3" UHD Direct-lit LED with HDR10 standard Retwork the whole Not Specifications: Display to and size: at least 44 C3" UHD Direct-lit LED with HDR10 standard Retwork the whole Not Specifications: Display to and size: at least 44 C3" UHD Direct-lit LED with HDR10 standard Retwork the whole Not Specifications: Display to and size: at least 44 C3" UHD Direct-lit LED with HDR10 standard Retwork the standard frame/view per device should find find find should b		Six (4) units Dome IP Camera						
supports #1.285 +, #2.85 video compression Varifocal Lens or Auto-focus, Capable of operating in both normal and poorly lit environment Weathers of a least IPES housing Weathers of Auto-focus, Capable of operating in both normal and poorly lit environment Weathers of Auto-focus of Intrason Detection / Line Crosaing Detection Usable with NVR recorder, PC Windows Software, or Medie Accepts PGE, 12V Do Power, or extended PoE Warrarny: 1 year One (1) unit Network Video Recorders Specifications: Specifications	1	Specifications:						-
Varifocal Lens or Auto-focus, Capable in Operating environment env		at least Full HD 1080 IP Cameras	of and construit					
Weatherpool of the intrinsion Detection / Line Crossing Advanced and Wild Recorder, PC Windows Software, or Mobile Applications to Accept Policy Windows Software, or Mobile Applications to Accept Policy Windows Software, or Mobile Applications (Accept Policy Windows Software, or Mobile Applications) (Accept Policy Warranty: 1 year One (1) unit Network Video Recorders Specifications: 16-CH (NVR) that support all CCTV cameras and with 2 units Surveillance Hard Drive 15-CH (NVR) that support all CCTV cameras and with 2 units Surveillance Hard Drive 15-CH (NVR) that support Applications such as but not interpreted System/Application for CCTV operations such as but not interpreted System/Application for CCTV operations such as but not interpreted System/Applications (Accept Policy	1	Varifocal Lens or Auto-focus, Capable of operating in bo	n normal and poorly lit					
Advanced Analytics: Intrusion betection betections Accepts PGE, 12V DC Power, or attended PGE Warranty: 1 year One (1) unit Network Video Recorders Specifications: 16-CR (NVR) that support all CCTV cameras and with 2 units Surveillance Hard Drive 17B Should have an Integrated System/Application for CCTV operations such as but not limited to real-dimentive view, video recording, remote search, playback, backup, etc. Third-party network summers, playback, backup, etc. Third-party network summers, playback, backup, etc. Third-party network summers, and the summers of th		environment						
Usable with NVR recorder, PV windows does Accepts Poit, 12V Dewar, or extended Pois Warranty: 1year One (1) unit Network Video Recorders Specifications: 16-CH (NVR) that support all CCTV cameras and with 2 units Surveillance Hard Drive 87B Should have an integrated System/Application for CCTV operations such as but not limited to real-timeflive view, video recording, remote search, playback, backup, etc. Third-party network cameras support 3 upport H.26s-Hr.264MPEG4 video formatise. Support 8 warranty: 1 year One (1) unit Poel Network Switch Specifications: unmanaged, 16 Gligabit Poil ports Power budget 2300V Warranty: 1 year One (1) unit Surveillance Smart TV Monitor Specifications: 5 x (ligabiteEhrenet, Dual Core 880MHz, 268MB RAM, USB, micro SD (optional) Warranty: 1 year One (1) unit Surveillance Smart TV Monitor Specifications: Display type and alzo: at least 4K 45" UHD Direct-lit LED with HDR10 standard Display type and alzo: at least 4K 45" UHD Direct-lit LED with HDR10 standard Display type and alzo: at least 4K 45" UHD Direct-lit LED with HDR10 standard Display type and store with the proposed number of OCTV cameras alimultaneously at the standard framewide yer device should include fixed wall bracket Warranty: 1 year One (1) unit USB Line Interactive Specifications: 2000VA1200W, 9 universal outlets, LCD display Warranty: 1 year One (1) unit USB Line Interactive Specifications: 2000VA1200W, 9 universal outlets, LCD display Warranty: 1 year One (1) unit USB Cline Interactive Specifications: 2000VA1200W, 9 universal outlets, LCD display Power-on delay: 7 yes, Over-voilage: 278Vac at 3A, RF suppressor: 7 yes, Ove		Advanced Analytics: Intrusion Detection / Line Crossing	Detection bile Applications					
One (1) unit Network Video Recorders Specifications: 16-CH (NVR) that support all CCTV cameras and with 2 units Surveillance Hard Drive 18-CH (NVR) that support all CCTV cameras and with 2 units Surveillance Hard Drive 18-CH (NVR) that support all CCTV cameras and with 2 units Surveillance Hard Drive 18-CH (NVR) that an Integrated System/Application for CCTM operations such as but not Specifications: United Party network cameras supported Support I. 26s-HJ.		THE WIND PACORDER PL WILLIAMS SOLITIONS	And the same of th					
One (1) unit Network Video Recorders Specifications: 18-CPL (NVR) that support all CCTV cameras and with 2 units Surveillance Hard Drive 18-TS Should have an Integrated System/Application for CCTM operations such as but not limited to real-dimentive view, video recording, remote search, playback, backup, etc. Illinoid-party network cameras supported Support H. 285-H/L 284/MPEG4 video formatise. Support Smart Search and Smart Playback Warranty: 1 year One (1) unit PoE Network Switch Specifications: unmanaged, 16 Gigabit POE ports Power budger 250W Warranty: 1 year One (1) unit Network Router Specifications: 5x GigabitElmenet, Dual Core 880MHz, 256MB RAM, USB, micro SD (optional) Warranty: 1 year One (1) unit Surveillance Smart TV Monitor Specifications: Display type and size: at least 4K 43" UHD Direct-lit LED with HDR10 standard Refresh Rate: 60 Hz Connectivity: HDMI, blatecoth, ethernet, SPDIF, USB, WIFI6 phrodic the sible to display all the proposed number of QCTV cameras simultaneously at the standard frame/low per device should include fixed wall bracket Warranty: 1 year One (1) unit UPS Line Interactive Specifications: 2000VA1200W, 6 universal outlets, LCD display Warranty: 1 year One (1) unit Power Surge Protector Specifications: 2000VA1200W, 8 Universal outlets, Cut-off voltage: 275Wa at 3A, RF suppressor: Yes, Over-ordage; Yes,		Warranty: 1 year						
Specifications: 18-CH (NVR) that support all CCTV cameras and with 2 units Surveillance Hard Drive 9TB Should have an integrated Systemi/Application for CCTV, operations such as but not limited to real-dimetrive view, video recording, remote search, playback, backup, etc. limited to real-dimetrive view, video recording, remote search, playback, backup, etc. Third-party network cameras supported Support N.285-M. 28-6/MPEG4 video formatse. Support Playback Warranty: 1 year One (1) unit PoE Network Switch Specifications: unmanaged, 16 (Gabit PoE ports Power budget 230W Warranty: 1 year One (1) unit Network Router Specifications: 8 x (GabitEthernet, Dual Core 850MHz, USB, micro SD (optional) Warranty: 2 year One (1) unit Surveillance Smart TV Monitor Specifications: 9 x (GabitEthernet, Dual Core 850MHz, 20 x (GabitEthernet, Politications) Roman State of the Connectivity: HDM, bluetooth, ethernet, SPDIF, USB, WFIS otherwide be able to usipally all the proposed number of GCTV cameras simultaneously at the standard frame/view per device should include fixed wall bracket Warranty: 1 year One (1) unit DPS Line Interactive Specifications: 2000 VA1 200W, 9 uniternational cutters, UCD display Warranty: 1 year One (1) unit Power Surge Protector Specifications: CU-Off voltage: 275Ve at 3A, RF suppressor: Ves, Over-voltage: 275Ve at 3A, RF suppressor: Ves, Over-voltage: 756Ve at 3A, PF suppressor: Ves,		Date 17 M						
Should have an Integrated System/Application for CCTV operations such as but not limited to real-dimetilive view, video recording, remote search, playback, backup, etc. limited to real-dimetilive view, video recording, remote search, playback, backup, etc. Third-party network cameras supported. Support 1,265-H. 264/MPEG4 video formatse. Support Smart Search and Smart Playback Warranty; 1 year One (1) unit PoE Network Switch Specifications: unmanaged, 16 (Gabit PoE ports Power budget 230W Warranty; 1 year One (1) unit Network Router Specifications: 5 x (GabitEthernet, Dual Core 880MHz, USB, micro SD (optional) Warranty; 286MB RAM, USB, micro SD (optional) Warranty; 1 year One (1) unit Surveillance Smart TV Monitor Specifications: Diaploy tipe and size: at least 4K 43" UHD Direct-lit LED with HDR10 standard Refresh Rate: 80 Hz Connectivity: HDML bluetooth, ethernet, SPDIF, USB, WFI6 otherwide be 30% to vilaple) at the proposed number of GCTV cameras simultaneously at the standard frame/view per device should include fixed wall bracket Warranty; 1 year One (1) unit UPS Line Interactive Specifications: 2000 VA1/200W, 0 unit-power Surge Protector Specifications: CU-off voltage: 275Vec at 3A, RF suppressor: Ves, Over-voltage: 275Vec at 3A, RF suppressor: Ves, Over-voltage: 275Vec at 3A, RP suppressor: Ves, Over-voltage: 275Vec at 3A, RP suppressor: Ves,		One (1) unit Network Video Recorders	II. B. mallings bland Delus					
Should have an Integrated System/Application for CCTV operations such as but not limited to real-dimetrive view, proceed proceeding, remote search, playback, backup, etc. Illimited to real-dimetrive view, proceedings are supported. System view of the view of		16-CH (NVR) that support all CCTV cameras and with 2	mits Surveillance Hard Drive					
Illimited to real-timenter view, visual supported Support Interface year, cameras a supported Support Interest. 254/MPEG4 video formatse. Support Playback Warranty: 1 year One (1) unit PoE Network Switch Specifications: unmanaged, 16 (sigabit PoE ports Power budget 230V Warranty: 1 year One (1) unit Network Router Specifications: 8 (sigabit PoE ports Power budget 230V Warranty: 1 year One (1) unit Network Router Specifications: 8 (sigabit Paide) 1558, micro SD (optional) Warranty: 1 year One (1) unit Surveillance Smart TV Monitor Specifications: Olipipity yea and size: at least 4K 43" UHD Direct-lit LED with HDR10 standard Refresh Reize of the Commercial Point Paide (1) unit Surveillance Smart TV Monitor Specifications: Olipipity yea and size: at least 4K 43" UHD Direct-lit LED with HDR10 standard Refresh Reize of the Commercial Point		6TB	operations such as but not				1	
Support N. 36-8-N. 264/MPEG4 video formatse. Support Smart Search and Smart Playback Warranty: 1 year One (1) unit PoE Network Switch Spacifications: unmanaged, 16 Gigabit PoE ports Power budget 2300W Warranty: 1 year One (1) unit Network Router Specifications: 56 GigabitEthernet, Dual Core 880MHz, 256MB RAM, USB, micro SD (optional) Warranty: 1 year One (1) unit Surveillance Smart TV Monitor Specifications: Display type and size: at least 4K 43" UHD Direct-lit LED with HDR10 standard Refresh Rate: 60 Hz. Connectivity: HDMI, Bluetooth, ethernet, SPDIF, USB, WIF15 rhroude the side to display all the proposed number of at the standard frame/live per device should include fixed wall bracket Warranty: 1 year One (1) unit UPS Line Interactive Specifications: 2000VA17200W, 6 universal outlets, LCD display Warranty: 1 year One (1) unit UPS Line Interactive Specifications: 2000VA17200W, 6 universal outlets, CLD display Warranty: 1 Year One (1) unit Power Surge Protector Specifications: Cut-off voltage: 275Vac at 3A, RF suppressor: Yes, Over-voltage protector: Yes, Power-on delay: Yes,	1	limited to real-time/live view, video recording	earch, playback, backup, etc.					
Playback Warranty: 1 year One (1) unit PoE Network Switch Specifications: unmanaged, 16 Gigabit PoE ports Power budget 230W Warranty: 1 year One (1) unit Network Router Specifications: 85 GigabitEthernet, Dual Core 880MHz, 286MB RAM, USB, micro SD (optional) Warranty: 1 year One (1) unit Surveillance Smart TV Monitor Specifications: Display type and size: at least 4K 43" UHD Direct-lit LED with HDR10 standard Refresh Rate: 60 Hz Connectivity: HDMI, bluetooth, ethernet, SPDIF, USB, WiFi5 78760/db be 86/e to display all the proposed number of GCTV cameras simultaneously at the standard frame/view per device should include fixed wall bracket Warranty: 1 year One (1) unit UPS Line Interactive Specifications: 2000VA/1200W, 6 universal outlets, LCD display Warranty: 1 year One (1) unit Power Surge Protector Specifications: Cut-off voltage: 275Vac at 3A, RF suppressor: Yes, Over-voltage protector: Yes, Power-on delay: Yes,								
Warranty: 1 year One (1) unit PoE Network Switch Specifications: ummanaged, 16 Gigabit PoE ports Power budget 230W Warranty: 1 year One (1) unit Network Router Specifications: 5x GigabitEthernet, Dual Core 880MHz, 266MB RAM, USB, micro SD (optional) Warranty: 1 year One (1) unit Surveillance Smart TV Monitor Specifications: Display type and size: at least 4K 43" UHD Direct-lit LED with HDR10 standard Refresh Rate: 80 Hz Connectivity: HDMI, bluetooth, ethernet, SPDIF, USB, WIF16 **Private to stapslay all the proposed number of GCTV cameras simultaneously at the standard frame/view per device should include fixed wall bracket Warranty: 1 year One (1) unit UPS Line Interactive Specifications: 2000/A/1200V, 6 universal outlets, LCD display Warranty: 1 year One (1) unit power Surge Protector Specifications: Cut-off voltage: 275Vac at 3A, RF suppressor: Yes, Over-voltage protector: Yes, Power-ondelay: Yes,		Playback						
Specifications: unmanaged, 16 Glaphit PoE ports Power budget 230W Warranty: 1 year One (1) unit Network Router Specifications: 5x GlaphitEthernet, Dual Core 880MHz, 266MB RAM, USB, micro SD (optional) Warranty: 1 year One (1) unit Surveillance Smart TV Monitor Specifications: Display type and size: at least 4K 43" UHD Direct-lift LED with HDR10 standard Refresh Rate: 60 Hz Connectivity: HDMI, bluetooth, ethernet, SPDIF, USB, WIFI5 Orkrotic Verbiev to display all the proposed number of GCTV cameras simultaneously at the standard frame/view per device should include fixed wall bracket Warranty: 1 year One (1) unit UPS Line Interactive Specifications: 2000VA/1200W, 6 universal outlets, LCD display Warranty: 1 year One (1) unit Power Surge Protector Specifications: Cut-off voltage: 276Vac at 3A, RF suppressor: Yes, Over-voltage protector: Yes, Power-on-delay: Yes,		Warranty: 1 year						
Specifications: unmanaged, 16 Glaphit PoE ports Power budget 230W Warranty: 1 year One (1) unit Network Router Specifications: 5x GlaphitEthernet, Dual Core 880MHz, 266MB RAM, USB, micro SD (optional) Warranty: 1 year One (1) unit Surveillance Smart TV Monitor Specifications: Display type and size: at least 4K 43" UHD Direct-lift LED with HDR10 standard Refresh Rate: 60 Hz Connectivity: HDMI, bluetooth, ethernet, SPDIF, USB, WIFI5 Orkrotic Verbiev to display all the proposed number of GCTV cameras simultaneously at the standard frame/view per device should include fixed wall bracket Warranty: 1 year One (1) unit UPS Line Interactive Specifications: 2000VA/1200W, 6 universal outlets, LCD display Warranty: 1 year One (1) unit Power Surge Protector Specifications: Cut-off voltage: 276Vac at 3A, RF suppressor: Yes, Over-voltage protector: Yes, Power-on-delay: Yes,		One (1) unit PoE Network Switch						
16 Gigabit POE ports Power budget 330W Warranty: 1 year One (1) unit Network Router Specifications: 6x GigabitEthernet, Dual Core 880MHz, 256MB RRM, USB, micro SD (optional) Warranty: 1 year One (1) unit Surveillance Smart TV Monitor Specifications: Display type and size: at least 4K 43" UHD Direct-lit LED with HDR10 standard Refresh Rate: 60 Hz Connectivity: HDMI, bluetooth, ethernet, SPDIF, USB, WIF15 nhred/d be able to tisplay all the proposed number of QCTV cameras simultaneously at the standard frame/view per device should include fixed wall bracket Warranty: 1 year One (1) unit UPS Line interactive Specifications: 2000VA1200W, 6 universal outlets, LCD display Warranty: 1 year One (1) unit Power Surge Protector Specifications: Cut-off votage: 275Vac at 3A, RF suppressor: Yes, Over-voltage protector: Yes, Power-on delay: Yes,		Specifications:						
Power budget 230W Warranty: 1 year One (1) unit Network Router Specifications: 5x GigabitEthernet, Dual Core 880MHz, 258MB RAM, USB, micro SD (optional) Warranty: 1 year One (1) unit Surveillance Smart TV Monitor Specifications: Display type and size: at least 4K 43" UHD Direct-lit LED with HDR10 standard Refreel Rate: 60 Hz Connectivity: HDMI, bluetooth, ethernet, SPDIF, USB, WIF15 shrudd be able to display all the proposed number of CCTV cameras simultaneously at the standard framelview per device should include fixed wall bracket Warranty: 1 year One (1) unit UPS Line Interactive Specifications: 2000VA/1200W, 6 universal outlets, LCD display Warranty: 1 year One (1) unit Power Surge Protector Specifications: Cut-off voltage: 275Vac at 3A, RF suppressor: Yes, Over-voltage protector: Yes, Power-on delay: Yes,								
One (1) unit Network Router Specifications: 5x GigabitEthernet, Dual Core 880MHz, 286MB RAM, USB, micro SD (optional) Warranty: 1 year One (1) unit Surveillance Smart TV Monitor Specifications: Display type and size: at least 4K 43" UHD Direct-lit LED with HDR10 standard Refresh Rate: 60 Hz Connectivity: HDMI, bluetooth, ethernet, SPDIF, USB, WIFIS https://docs.org/splay/apid/splay/apid/splay/apid/splay/apid/splay/apid/splay/apid/splay/apid/splay/apid/splay/apid/splay/apid/splay/apid/splay/apid/splay/apid/splay/apid/splay/splay/apid/splay/splay/apid/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/splay/s		Power budget 230W						
Specifications: 5x GigabitEthernet, Dual Core 880MHz, 286MB RAM, USB, micro SD (optional) Warranty: 1 year One (1) unit Surveillance Smart TV Monitor Specifications: Display type and size: at least 4K 43" UHD Direct-lit LED with HDR10 standard Refresh Rate: 60 Hz Connectivity: HDMI, bluetooth, ethernet, SPDIF, USB, WiF15 'whrow'd be abide to display all the proposed number of GCTV cameras simultaneously at the standard frame/view per device should include fixed wall bracket Warranty: 1 year One (1) unit UPS Line Interactive Specifications: 2000/VA/1200W, 6 universal outlets, LCD display Warranty: 1 year One (1) unit Power Surge Protector Specifications: Cut-off voltage: 278Vac at 3A, RF suppressor: Yes, Over-voltage protector: Yes, Power-on delay: Yes,		Warranty: 1 year		1				
5x GigabitEthernet, Dual Core 880MHz, 256MB RAM, USB, micro SD (optional) Warranty: 1 year One (1) unit Surveillance Smart TV Monitor Specifications: Display type and size: at least 4K 43" UHD Direct-lit LED with HDR10 standard Refresh Rate: 60 Hz Connectivity: HDMI, bluetooth, ethernet, SPDIF, USB, Shrudro be able to display all the proposed number of at the standard frame/view per device should include fixed wall bracket Warranty: 1 year One (1) unit UPS Line Interactive Specifications: 2000VA/1200W, 6 universal outlets, LCD display Warranty: 1 year One (1) unit Power Surge Protector Specifications: Cut-off voltage: 275Vac at 3A, RF suppressor: Yes, Over-voltage protector: Yes, Power-on delay: Yes,								
Dual Core 880MHz, 256MB RAM, USB, micro SD (optional) Warranty: 1 year One (1) unit Surveillance Smart TV Monitor Specifications: Display type and size: at least 4K 43" UHD Direct-lit LED with HDR10 standard Refresh Rate: 50 Hz Connectivity: HDMI, bluetooth, ethernet, SPDIF, USB, WIF15 **Throwin's to state to display all the proposed number of QCTV cameras simultaneously at the standard framely-lew per device should include fixed wall bracket Warranty: 1 year One (1) unit UPS Line Interactive Specifications: 2000VA/1200W, 8 universal outlets, LCD display Warranty: 1 year One (1) unit Power Surge Protector Specifications: Cut-off voltage: 276Vac at 3A, RF suppressor: Yes, Over-voltage protector: Yes, Power-on delay: Yes,								
Warranty: 1 year One (1) unit Surveillance Smart TV Monitor Specifications: Display type and size: at least 4K 43" UHD Direct-lit LED with HDR10 standard Refresh Rate: 60 Hz Connectivity: HDMI, bluetooth, ethernet, SPDIF, USB, WIFI5 'shruch' be able to display all the proposed number of CCTV cameras simultaneously at the standard framelview per device should include fixed wall bracket Warranty: 1 year One (1) unit UPS Line Interactive Specifications: 2000VA/1200W, 6 universal outlets, LCD display Warranty: 1 year One (1) unit Power Surge Protector Specifications: Cut-off voltage: Z75Vac at 3A, RF suppressor: Yes, Over-voltage protector: Yes, Power-on delay: Yes,		Dual Core 880MHz,						
One (1) unit Surveillance Smart TV Monitor Specifications: Display type and size: at least 4K 43" UHD Direct-lit LED with HDR10 standard Refresh Rate: 80 Hz Connectivity: HDMI, bluetooth, ethernet, SPDIF, USB, WIFI5 Throwing be able to display all the proposed number of CCTV cameras simultaneously at the standard frame/view per device should include fixed wall bracket Warranty: 1 year One (1) unit UPS Line Interactive Specifications: 2000VA/1200W, 6 universal outlets, LCD display Warranty: 1 year One (1) unit Power Surge Protector Specifications: Cut-off voltage: 275Vac at 3A, RF suppressor: Yes, Over-voltage protector: Yes, Power-on delay: Yes,		AND THE PROPERTY OF THE PROPER						
Specifications: Display type and size: at least 4K 43" UHD Direct-lit LED with HDR10 standard Refresh Rate: 80 Hz Connectivity: HDMI, bluetooth, ethernet, SPDIF, USB, WIFI5 Phrech's the abile to display all the proposed number of GCTV cameras simultaneously at the standard frame/view per device should include fixed wall bracket Warranty: 1 year One (1) unit UPS Line Interactive Specifications: 2000VA/1200W, 8 universal outlets, LCD display Warranty: 1 year One (1) unit Power Surge Protector Specifications: Cut-off voltage: 275Vac at 3A, RF suppressor: Yes, Over-voltage protector: Yes, Power-on delay: Yes,								
Display type and size: at least 4K 43" UHD Direct-lit LED with HDR10 standard Refresh Rate: 60 Hz Connectivity: HDMi, bluetooth, ethernet, SPDIF, USB, WIF15 Phrough be able to display all the proposed number of CCTV cameras simultaneously at the standard frame/view per device should include fixed wall bracket Warranty: 1 year One (1) unit UPS Line Interactive Specifications: 2000VA/1200W, 6 universal outlets, LCD display Warranty: 1 year One (1) unit Power Surge Protector Specifications: Cut-off voltage: 275Vac at 3A, RF suppressor: Yes, Over-voltage protector: Yes, Power-on delay: Yes,								
Refresh Rate: 60 Hz Connectivity: HDMI, bluetooth, ethernet, SPDIF, USB, WiFi5 Chreck to display all the proposed number of CCTV cameras simultaneously at the standard frame/view per device should include fixed wall bracket Warranty: 1 year One (1) unit UPS Line interactive Specifications: 2000VA/1200W, 6 universal outlets, LCD display Warranty: 1 year One (1) unit Power Surge Protector Specifications: Cut-off voltage: 275Vac at 3A, RF suppressor: Yes, Over-voltage protector: Yes, Power-on delay: Yes,		Display type and size: at least 4K 43" UHD Direct-lit LE	D with HDR10 standard				į	
at the standard frame/view per device should include fixed wall bracket Warranty: 1 year One (1) unit UPS Line Interactive Specifications: 2000VA/1200W, 6 universal outlets, LCD display Warranty: 1 year One (1) unit Power Surge Protector Specifications: Cut-off voltage: 275Vac at 3A, RF suppressor: Yes, Over-voltage protector: Yes, Power-on delay: Yes,		Refresh Rate: 60 Hz						
at the standard frame/view per device should include fixed wall bracket Warranty: 1 year One (1) unit UPS Line Interactive Specifications: 2000VA/1200W, 6 universal outlets, LCD display Warranty: 1 year One (1) unit Power Surge Protector Specifications: Cut-off voltage: 275Vac at 3A, RF suppressor: Yes, Over-voltage protector: Yes, Power-on delay: Yes,	Į.			.				
Warranty: 1 year One (1) unit UPS Line Interactive Specifications: 2000VA/1200W, 6 universal outlets, LCD display Warranty: 1 year One (1) unit Power Surge Protector Specifications: Cut-off voltage: 275Vac at 3A, RF suppressor: Yes, Over-voltage protector: Yes, Power-on delay: Yes,		at the standard frame/view per device					1	
One (1) unit UPS Line Interactive Specifications: 2000VA/1200W, 6 universal outlets, LCD display Warranty: 1 year One (1) unit Power Surge Protector Specifications: Cut-off voltage: 275Vac at 3A, RF suppressor: Yes, Over-voltage protector: Yes, Power-on delay: Yes,								
Specifications: 2000VA/1200W, 6 universal outlets, LCD display Warranty: 1 year One (1) unit Power Surge Protector Specifications: Cut-off voltage: 275Vac at 3A, RF suppressor: Yes, Over-voltage protector: Yes, Power-on delay: Yes,		One (1) unit UPS Line Interactive					-	
6 universal outlets, LCD display Warranty: 1 year One (1) unit Power Surge Protector Specifications: Cut-off voltage: 275Vac at 3A, RF suppressor: Yes, Over-voltage protector: Yes, Power-on delay: Yes,		Specifications:						
LCD display Warranty: 1 year One (1) unit Power Surge Protector Specifications: Cut-off voltage: 275Vac at 3A, RF suppressor: Yes, Over-voltage protector: Yes, Power-on delay: Yes,								
One (1) unit Power Surge Protector Specifications: Cut-off voltage: 275Vac at 3A, RF suppressor: Yes, Over-voltage protector: Yes, Power-on delay: Yes,		LCD display						
Specifications: Cut-off voltage: 275Vac at 3A, RF suppressor: Yes, Over-voltage protector: Yes, Power-on delay: Yes,		Warranty: 1 year						
Specifications: Cut-off voltage: 275Vac at 3A, RF suppressor: Yes, Over-voltage protector: Yes, Power-on delay: Yes,		One (1) unit Power Surge Protector						
RF suppressor: Yes, Over-voltage protector: Yes, Power-on delay: Yes,	1	Specifications:						
Over-voltage protector: Yes, Power-on delay: Yes,								
		Over-voltage protector: Yes,						
							-	
	2	,		10	1.		(8)	

Spical Sp	s (1) box Outdoor UTP Cable scifications: :6 UTP solid copper AWG SM ty (50) pieces RJ-45 Connector ecifications: t.6 ne (1) unit Data Cabinet secifications: t, 600 x 450mm, th 2 fans, way PDU, sets cage nut (optional) ight (8) pieces Terminal Junction Box pecifications: 6 65 Phite 50x150x70mm Vith Screw at the 4 angle ussorted Sizes Wire Clips Round (white) 150pcs 9mm 50pcs 16mm 50pcs 20mm Assorted Sizes Tie Wrap (white) -100pcs 4Inch -100pcs 6inch -100pcs 10inch Please see attached Terms of Reference				
			Т	OTAL PRICE	
			COMPLIANC	CE	REMARKS
	OTHER REQUIRE	MENTS	Can Comply	Cannot Comply	112.11
	Delivery of Goods is within 5 working days after place at DSWD FO CAR, #40 NORTH Drive,Bagu Saturday/Sunday/Holiday, the delivery of goods of	an be moved to the next working day.	[]	[]	
	Service Provider must have Active Landbank Accibanks, service charge will be deducted upon pay	ment on the account.	[]	[]	
	PAYMENT	SHALL BE MADE THRU LAND	BANK OF THE PHILIP	PINES	
	Award shall be	made per: Item Bas	is X Lot Bas	IS act any or all offers at no costs	, waive any therein and
accept the off	 Award shall be <u>TALLOWED</u>. Pursuant to RA 6713, otherwise known as the Code of Ca fer most advantageous to the government. 				
Sir:	After having carefully read and accept	Name of Firm/Dealer,	/Contractor:	item/s quoted ab	ove.
	Owner	s/Proprietor/President's Name an			
		515,79963375	t Number/s: nail Address:		
	For Aught and	2 22 22 22			
	For Authorize	d Representative, kindly indicate th	d Signature:		
		Name an			
		DLUCE	Contact Number/s:		
		PhilGE	PS Registration Number:		

Name and Signature of Canvasser





"DSWD-GF-004 | REV 03 | 22 SEP 2023

TERMS OF REFERENCE FOR HIRED SERVICE PROVIDERS

IDENTI	FYING INFORMATION			
Title: PURCHASE AND DELIVERY OF CCTV HARDWARE FOR SWAD ABRA				
Delivery Location: DSWD-CAR #40 North Drive, Baguio City				
Duration: April 2025				
TERMS AND CONDITIONS Statement of Compliance 1. Due to the urgency of the project, delivery	is within five (5) working days after receipt of Purchase Order.			
2. The bidder can comply with the Schedule Note: Schedule of Requirements shall be condition.	Schedule of Requirements shall be attached to support compliance to this specific terms and			
field office during the warranty period.				
presented during the post qualification stage	sed brand should at least be ISO 9000 certified or better (proof shall be tion stage).			
years.	sold and marketed continuously in the Philippines for the last ten (10)			
6. The procuring entity reserves the right to cancel the contract or reduce the quantity of the goods for any justifiable reasons or for any circumstance beyond the procuring entity's control, i.e. force majeure, fortuitous events, etc.				
7. Payment Term: Payment will be processe supporting documents.	ed upon complete delivery of items and submission of complete			
Prepared by:	Concurred by:			
MARY ANTONETTE A. PARDO	Service Provider:			
Reviewed by: MARVIN F. GAMBOA ITO II Section Head	(Printed Name over Signature) Address:			
Approved by: ENRIQUE H. GASCON, JR. DIRECTOR III ARD for Administration, OARDA	Contact Number:			