

SUPPLEMENTAL / BID BULLETIN NO. 01

TITLE : Purchase and Delivery of Carpentry, Electrical, Plumbing, and Other Supplies, Tools, and Equipment
ITB NO. : 2025-DSWD-CAR-26
DATE : 01 December 2025

This Supplemental/Bid Bulletin is issued to all prospective bidders announcing the following:

Description	From	To
Invitation to Bid (Item No. 2)	2. The Department of Social Welfare and Development - CAR now invites bids for the above Procurement Project. Delivery of the Goods is required <i>within twenty (20) calendar days upon receipt of the Notice to Proceed.</i> xxx.	2. The Department of Social Welfare and Development - CAR now invites bids for the above Procurement Project. Delivery of the Goods is required <i>within thirty (30) calendar days upon receipt of the Notice to Proceed.</i> xxx.
Bid Data Sheet (Clause 20.2)	<p><u>The Lowest Calculated Bid (LCB) or Single Calculated Bid (SCB) as the case may be shall submit the following additional documents during the Post-Qualification Stage:</u></p> <ol style="list-style-type: none"> 1. <u>Valid and current Certificate Product Registration (CPR) or Certificate of Medical Device Registration (CMDR) or Certificate of Exemption or Certificate of Medical Device Notification (CMDN) issued by Philippine Food and Drug Administration (PFDA);</u> 2. <u>Valid and current License to Operate (LTO) as Medical Device Importer/ Wholesaler issued by Philippine Food and Drug Administration (PFDA);</u> 3. <u>Valid and current License to Operate (LTO) as Drug Distributor/Importer/Wholesaler issued by Philippine Food and Drug Administration (PFDA);</u> 4. <u>The bidder shall submit any of the following whichever is applicable:</u> <ol style="list-style-type: none"> a. <u>If the bidder is a manufacturer, certify that the bidder manufactures the products/items;</u> or 	<p><u>In support to the Statement of All Ongoing Government and Private Contracts the following documents shall be submitted as part of the post qualification requirement:</u></p> <ol style="list-style-type: none"> 1. <u>Notice of Award and/or Contract/Purchase Order</u> 2. <u>Notice to Proceed (for government transactions only under Public Bidding)</u> <p><u>In support to the Statement of Single Largest Completed Contracts (SLCC) the following documents shall be submitted as part of the post qualification requirement:</u></p> <ol style="list-style-type: none"> 1. <u>Statement of Single Largest Completed Contracts (SLCC) shall be supported with End-user's Acceptance or Official Receipts¹ or Sales Invoice;</u> 2. <u>In case a Collection Receipt is available in lieu of Official Receipt, such should be supported with the necessary invoice receipt like Charge Invoice.</u>

Description	From	To
	<p><u>b. If the bidder is an Exclusive/ Authorized Distributor or Dealer of the products/items, Certificate or Contract from the manufacturer must be provided as proof that the bidder is an Exclusive/ Authorized Distributor or Dealer of the products/items; or</u></p> <p><u>c. If the bidder is an agent of the exclusive distributor or dealer, the following must be provided:</u></p> <p><u>i. Certificate or Distributorship/ Dealership Agreement by the Manufacturer with the distributor or dealer; or</u></p> <p><u>ii. Contract between the distributor/ dealer and the bidder.</u></p> <p>In support to the Statement of All Ongoing Government and Private Contracts the following documents shall be submitted as part of the post qualification requirement:</p> <ol style="list-style-type: none"> 1. Notice of Award and/or Contract/Purchase Order 2. Notice to Proceed (for government transactions only under Public Bidding) <p>In support to the Statement of Single Largest Completed Contracts (SLCC) the following documents shall be submitted as part of the post qualification requirement:</p> <ol style="list-style-type: none"> 1. Statement of Single Largest Completed Contracts (SLCC) shall be supported with End-user's Acceptance or Official Receipts¹ or Sales Invoice; 2. In case a Collection Receipt is available in lieu of Official Receipt, such should be supported with the necessary invoice receipt like Charge Invoice. 	
<p>Schedule of Requirements (Delivery Period)</p>	<p><i>Within <u>twenty (20)</u> calendar days upon receipt of the Notice to Proceed.</i></p>	<p><i>Within <u>thirty (30)</u> calendar days upon receipt of the Notice to Proceed.</i></p>

Description	From	To
Technical Specifications (I. CARPENTRY SUPPLIES, TOOLS, AND EQUIPMENT, Item No. 15)	Brushless Cordless 4" Angle Grinder 20V Max XR Li-ion Kit Set Voltage 20V Max Battery Cell Type Lithium-Ion Disc Diameter 100mm Spindle Thread M10 Switch Type Slider No Load Speed 9,000 RPM Soft Start Yes E-clutch Yes E-brake Yes INCLUDES: 1 x Brushless Cordless 4" Angle Grinder 20V 2 x 5.0Ah Battery 1 x Charger 1 x Side Handle 1 x TSTAK Toolbox	Brushless Cordless 4" Angle Grinder 20V Li-ion Kit Set Voltage 20V Max Battery Cell Type Lithium-Ion Disc Diameter 100mm Spindle Thread M10 Switch Type Slider No Load Speed 9,000 RPM Soft Start Yes E-clutch Yes E-brake Yes INCLUDES: 1 x Brushless Cordless 4" Angle Grinder 20V 2 x 5.0Ah Battery 1 x Charger 1 x Side Handle 1 x TSTAK Toolbox

Please refer to the attached revised forms:

1. Invitation to Bid
2. Bid Data Sheet
3. Schedule of Requirements
4. Technical Specifications

Changes indicated in the Bid Bulletin shall form part of the bidding documents.

Please be guided accordingly.


 F. ENGR. ENRIQUE H. GASCON JR.
 BAC Chairperson

Bid Data Sheet

ITB Clause							
5.3	<p>For this purpose, contracts similar to the Project shall be:</p> <p>a. Purchase and Delivery of Carpentry, Electrical, Plumbing, and Other Supplies, Tools, and Equipment</p> <p>b. Completed within two (2) years prior to the deadline for the submission and receipt of bids.</p>						
7.1	<i>Not applicable</i>						
12	The price of the Goods shall be quoted in DDP <i>Baguio City, Philippines</i> or the applicable International Commercial Terms (INCOTERMS) for this Project.						
14.1	<p>The bid security shall be in the form of a Bid Securing Declaration, or any of the following forms and amounts:</p> <p>a. The amount of not less than 2% of the ABC, if bid security is in cash, cashier's/manager's check, bank draft/guarantee or irrevocable letter of credit; or</p> <p>b. The amount of not less than 5% of the ABC, if bid security is in Surety Bond.</p>						
19.3	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center;">Lot No.</th> <th style="text-align: center;">Description</th> <th style="text-align: center;">ABC</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">Lot 1</td> <td>Purchase and Delivery of Carpentry, Electrical, Plumbing, and Other Supplies, Tools, and Equipment</td> <td style="text-align: center;">PhP 2,147,543.52</td> </tr> </tbody> </table>	Lot No.	Description	ABC	Lot 1	Purchase and Delivery of Carpentry, Electrical, Plumbing, and Other Supplies, Tools, and Equipment	PhP 2,147,543.52
Lot No.	Description	ABC					
Lot 1	Purchase and Delivery of Carpentry, Electrical, Plumbing, and Other Supplies, Tools, and Equipment	PhP 2,147,543.52					
20.2	<p>In support to the Statement of All Ongoing Government and Private Contracts the following documents shall be submitted as part of the post qualification requirement:</p> <ol style="list-style-type: none"> 1. Notice of Award and/or Contract/Purchase Order 2. Notice to Proceed (for government transactions only under Public Bidding) <p>In support to the Statement of Single Largest Completed Contracts (SLCC) the following documents shall be submitted as part of the post qualification requirement:</p> <ol style="list-style-type: none"> 1. Statement of Single Largest Completed Contracts (SLCC) shall be supported with End-user's Acceptance or Official Receipts¹ or Sales Invoice; 2. In case a Collection Receipt is available in lieu of Official Receipt, such should be supported with the necessary invoice receipt like Charge Invoice. 						
21.1	<i>Not Applicable</i>						

Section VI. Schedule of Requirements

The delivery schedule expressed as weeks/months stipulates hereafter a delivery date which is the date of delivery to the project site.

Lot No.	Description	Qty / Unit	Delivery Place	Delivery Period
1	Purchase and Delivery of Carpentry, Electrical, Plumbing, and Other Supplies, Tools, and Equipment	1 LOT	DSWD Field Office CAR #40 North Drive, Baguio City	Within <u>within Thirty (30) calendar days upon receipt of the Notice to Proceed.</u>

Note: Please refer to Section VII. Technical Specifications for the itemized list of Medicines and Medical Supplies

Section VII. Technical Specifications

Notes for Preparing the Technical Specifications

A set of precise and clear specifications is a prerequisite for Bidders to respond realistically and competitively to the requirements of the Procuring Entity without qualifying their Bids. In the context of Competitive Bidding, the specifications (*e.g.* production/delivery schedule, manpower requirements, and after-sales service/parts, descriptions of the lots or items) must be prepared to permit the widest possible competition and, at the same time, present a clear statement of the required standards of workmanship, materials, and performance of the goods and services to be procured. Only if this is done will the objectives of transparency, equity, efficiency, fairness, and economy in procurement be realized, responsiveness of bids be ensured, and the subsequent task of bid evaluation and post-qualification facilitated. The specifications should require that all items, materials and accessories to be included or incorporated in the goods be new, unused, and of the most recent or current models, and that they include or incorporate all recent improvements in design and materials unless otherwise provided in the Contract.

Samples of specifications from previous similar procurements are useful in this respect. The use of metric units is encouraged. Depending on the complexity of the goods and the repetitiveness of the type of procurement, it may be advantageous to standardize the General Technical Specifications and incorporate them in a separate subsection. The General Technical Specifications should cover all classes of workmanship, materials, and equipment commonly involved in manufacturing similar goods. Deletions or addenda should then adapt the General Technical Specifications to the particular procurement.

Care must be taken in drafting specifications to ensure that they are not restrictive. In the specification of standards for equipment, materials, and workmanship, recognized Philippine and international standards should be used as much as possible. Where other particular standards are used, whether national standards or other standards, the specifications should state that equipment, materials, and workmanship that meet other authoritative standards, and which ensure at least a substantially equal quality than the standards mentioned, will also be acceptable. The following clause may be inserted in the Special Conditions of Contract or the Technical Specifications.

Sample Clause: Equivalency of Standards and Codes

Wherever reference is made in the Technical Specifications to specific standards and codes to be met by the goods and materials to be furnished or tested, the provisions of the latest edition or revision of the relevant standards and codes shall apply, unless otherwise expressly stated in the Contract. Where such standards and codes are national or relate to a particular country or region, other authoritative standards that ensure substantial equivalence to the standards and codes specified will be acceptable.

Reference to brand name and catalogue number should be avoided as far as possible; where unavoidable they should always be followed by the words "*or at least equivalent.*" References to brand names cannot be used when the funding source is the GOP.

Where appropriate, drawings, including site plans as required, may be furnished by the Procuring Entity with the Bidding Documents. Similarly, the Supplier may be requested to provide drawings or samples either with its Bid or for prior review by the Procuring Entity during contract execution.

Bidders are also required, as part of the technical specifications, to complete their statement of compliance demonstrating how the items comply with the specification.

Technical Specifications

Item	Qty	Unit	Specification	Statement of Compliance
				<p><i>[Bidders must state here either "Comply" or "Not Comply" against each of the individual parameters of each Specification stating the corresponding performance parameter of the equipment offered (including the prescribed terms and conditions). Statements of "Comply" or "Not Comply" must be supported by evidence in a Bidders Bid and cross-referenced to that evidence. Evidence shall be in the form of manufacturer's un-amended sales literature, unconditional statements of specification and compliance issued by the manufacturer, samples, independent test data etc., as appropriate. A statement that is not supported by evidence or is subsequently found to be contradicted by the evidence presented will render the Bid under evaluation liable for rejection. A statement either in the Bidder's statement of compliance or the supporting evidence</i></p>

Item	Qty	Unit	Specification	Statement of Compliance
				<i>that is found to be false either during Bid evaluation, post-qualification or the execution of the Contract may be regarded as fraudulent and render the Bidder or supplier liable for prosecution subject to the applicable laws and issuances.]</i>
I. CARPENTRY SUPPLIES, TOOLS, AND EQUIPMENT				
1	40	set	Door Knob Lockset -Heavy Duty, Lever type	
2	5	set	Screw Driver Set -6 pc heavy duty carbon steel -Cushion Grip -Magnetic Tip -Phillips (3/16", 1/4") -Flat (3/16", 1/4")	
3	4	pcs	Crosscut Saw -Machine set and sharpened teeth for accurate cutting. -High carbon steel blade hardened and tempered for sharpness and durability. -Comes with full length sleeve. -18" (20-502)	
4	4	pcs	Rubber Grip Hacksaw Frame Steel frame with better locking system, and includes aluminum handle for better positioning 10-inch hacksaw with rigid steel frame and molded rubber cushion grip D-shaped guard protects hands and knuckles Fully adjustable frame Throat depth of 3-7/8 inches	
5	4	pcs	Caulking Gun -Aluminum body with steel trigger -Size: 9 inches, 230mm -High quality & Heavy duty	
6	4	pcs	Pipe wrench 12" -Size: 12" (300mm) -Max Clamping Diameter: 42mm -Jaw Material: Mobile jaw drop-forged with high-quality carbon steel -Treatment: Inactivate treatment -Body Material: Ductile cast iron -Finish: Black finish and polished solid rivet	

Item	Qty	Unit	Specification	Statement of Compliance
7	4	pcs	Pipe Wrench 18" Size: 18" (450mm) Maximum Clamping Diameter: 60mm Jaw Material: Drop-forged high-quality carbon steel Body Material: Ductile cast iron Finish: Black finish and polish	
8	4	pcs	Claw Hammer Fiberglass Handle Slip resistant handle	
9	2	pcs	Sledgehammer Heavy Duty 8 lbs. Slip resistant Handle	
10	5	pcs	Torpedo Level 9" Magnetic, High Impact ABS Top-reading, Tinted 360° vial for readability Plastic torpedo level	
11	7	unit	19" 3-Level Essential Cantilever Tool Box -3 LEVELS OF STORAGE: For easy access to your tools and accessories. -2 INTERNAL TRAYS: For quick organization and accessibility to smaller hand tools. -2 LID ORGANISER COMPARTMENTS: For storage of small fixings and accessories. -METAL LATCHES: For durability. -PULL HANDLE: For easy tool box closure. -PADLOCK EYE: For security. -TEXTURED CARRY HANDLE: For comfort and easy transportation.	
12	4	set	Combination Wrench Set 11 pcs (8,10,11,12,13,14,17,19,21,22,24 mm) Wipes clean easily Large size markings for readability 12-Points on the closed end of the wrench	
13	2	pcs	Hand Riveter (Swivel Head) -360° Swivel Head -Durable Construction -Ergonomic Design -Versatile Compatibility -Easy Operation	
14	1	unit	Digital Inverter IGBT Arc Welding Machine -Includes Electrode Holder, Ground Clamp and Hand Type Welding Mask	

Item	Qty	Unit	Specification	Statement of Compliance
			-Uses Insulated Gate Bipolar Transistor Technology (IGBT) -Portable Welding Machine - 300 Amperes -Power Voltage (V) 220 V -Rated Input Capacity (kVA) 3.8 kVA -Input Voltage Frequency (Hz) 60 Hz -No-Load Voltage 65 V -Output Current Range (A) 10 – 300 A -Duty Cycle (%) 60.0 % -Efficiency (%) 85.0 % -Insulation Class F -Protection Class IP21S -ISO 9001 Certified Yes	
15	1	set	Brushless Cordless 4" Angle Grinder 20V Li-ion Kit Set Voltage 20V Max Battery Cell Type Lithium-Ion Disc Diameter 100mm Spindle Thread M10 Switch Type Slider No Load Speed 9,000 RPM Soft Start Yes E-clutch Yes E-brake Yes INCLUDES: 1 x Brushless Cordless 4" Angle Grinder 20V 2 x 5.0Ah Battery 1 x Charger 1 x Side Handle 1 x TSTAK Toolbox	
16	1	set	13 Pcs/Set Bi-Metal Hole Saw Set with Case Model: AKH0132 13 Pcs Bi-metal hole saw set Material: HSS M3 Bi-metal Size: 19mm(3/4")/22mm(7/8")/29mm(1-1/8")/35mm(1-3/8")/38mm(1-1/2")/44mm(1-3/4")/51mm(2")/57mm(2-1/4")/64mm(2-1/2") 1pc x Arbor: 3/8" Hex Shank, Fit Size: 9/16"~1-3/16" 1pc x Arbor: 7/16" Hex Shank, Fit Size: 1-1/4"~8-17/64" 1pc x Adapter arbors with 1/2-20 threads to fit hole saws 5/8-18 threads 1pc x Pilot drill 1pc x Hex key wrench	
17	1	unit	Laser Distance Detector with Measuring Range: 0.05-50m Measuring Range: 0.05-50m Measuring Accuracy: ±2.0mm	

Item	Qty	Unit	Specification	Statement of Compliance
			Laser Type: 635nm, <1mW, Class 2 Function: single measurement/continuous measurement/indirect measurement/area measurement/Volume measurement/single Pythagorean theorem measurement/double Pythagorean plus/double area measurement Battery: 2*1.5 AAA Operating temp: 0°C ~ +50°C	
18	1	set	12 Pcs Flat Wood Drill Bits Set Product Type: 12 pcs Flat Wood Drill Bits Set Set Includes: 12 pcs Sizes: 6 mm, 8 mm, 10 mm, 12 mm, 14 mm, 16 mm, 18 mm, 20 mm, 25 mm, 28 mm, 30 mm, 32 mm Shank Size: 1/4" hex Length: 152 mm	
19	1	set	P20S/20V 2 PCS/Set Lithium-Ion Cordless & Corded Palm Sander Combo Kit Rated Voltage: 20V Cordless Sheet Sander (CSHSLI2014): No-load Speed: 12,000rpm Bottom Size: 110mm x 100mm (4-3/8" x 4") Palm Sander (PS2416): Rated Voltage: 220-240V~50/60Hz Input Power: 240W No-load Speed: 14,000rpm Bottom Base: 110mm x 100mm (4-3/8" x 4") Features: 50pcs x Sandpaper 1 Set Extra Carbon Brushes 1pc x 2.0Ah Battery Pack (FBLI20011) 1pc x Charger (FCLI2001) Charge Volts: 220-240V~50/60Hz	
20	1	set	7 Pcs Steel Magnetic Welding Holder Set/ Angle Welding Magnets Set Includes: 7 pcs (4 different sizes) Compatible Angles: 30°, 45°, 75°, 105°, 120°, 135° Sizes: Small Dimensions: 2.8 inches (70 mm) x 0.5 inches (12 mm) x 1.7 inches (42.5 mm) Medium (Multi-Angle) Dimensions: 4.6 inches (117 mm) x 0.7 inches (17.1 mm) x 3.5 inches (90 mm)	

Item	Qty	Unit	Specification	Statement of Compliance
			Medium Dimensions: 4.7 inches (120 mm) x 0.6 inches (14.4 mm) x 3.3 inches (83 mm) Large Dimensions: 6.1 inches (155 mm) x 0.7 inches (17.4 mm) x 4.0 inches (102 mm)	
21	2	set	Allen Wrench Set 9 pcs per set Long arm Double End (Flat End/Ball End)	
22	2	pair	Welding Gloves Heavy Duty Welding Gloves 16" Fire/Heat Resistant and cut resistant	
23	2	pcs	Double Socket Wrench Double Socket Ratchet Wrench 17mm x 19mm CRV socket with 12 points Drop forged steel body Black finished Heat treatment	
24	30	pcs	S4S Lumber 2" x 2" x 8ft (height)	
25	30	pcs	S4S Lumber 2" x 3" x 8ft (height)	
26	20	pcs	Angle Bar 50mm x 50mm x 4mm thick x 6m length	
27	20	pcs	Angle Bar 38mm x 38mm x 4mm thick x 6m length	
28	1	set	Cordless and Brushless Impact Drill Rated Voltage: 20V above No-load Speed: 0-2300rpm above Max. Torque: 300 N.M above Impact Per Minutes: 0-3300/min above With extra battery and charger With Impact Socket Set (1/2" - 10mm,12mm,13mm,14mm,17mm,19mm,21mm,22mm and 24mm) Screwdriver Bits (10 pcs)	
29	1	set	Wood Planer with complete accessories Continuous rating input 580W Planing Width 82 mm (3-1/4") Planing Depth 1 mm (1/32") Max Shiplapping 9 mm (11/32") No Load Speed (RPM) 16,000 Vibration Level: Planing Softwood 3.0 m/s ² Sound Pressure Level 84 dB(A) Sound Power Level 95 dB(A) Dimensions (L x W x H) 285x157x160 mm Net weight (11-1/4"x6-3/16"x6-5/16")	

Item	Qty	Unit	Specification	Statement of Compliance
			Power supply cord 2.6 – 2.7 kg (5.7 – 6.0 lbs)	
30	1	set	Heavy Duty Top Handle Corded Jigsaw Continuous rating input 450W Max Cutting Capacity at 90° Wood: 55 mm (2-3/16"), Steel: 6 mm (1/4") Length of Stroke 26 mm (1") Strokes Per Minute (SPM) 0 – 3,100 Vibration Level Cutting Boards: 6.5 m/s ² Sound Pressure Level 88 dB(A) Sound Power Level 99 dB(A) Net weight 2.5 kg (5.5 lbs.)	
31	1	set	Heavy Duty Cordless Jigsaw INCLUDES: Fast Charger and BL1860B 6.0Ah Lithium-Ion Battery and Charger 18V LXT Set Battery voltage 18.0 V Weight excl. battery 2 kg Stroke rate at no load 0 – 3,500 spm Stroke height 26 mm Cutting depth in wood 125 mm Cutting depth in aluminium 20 mm Cutting depth in unalloyed steel 10 mm	
32	2	pcs	Hand Riveter (Swivel Head) 360° Swivel Head Durable Construction Ergonomic Design Versatile Compatibility Easy Operation	
33	2	pcs	Rubber Grip Hacksaw Frame Includes hacksaw blade Hacksaw cutting tool has a steel frame with better locking system, and includes aluminum handle for better positioning 10-inch hacksaw with rigid steel frame and molded rubber cushion grip D-shaped guard protects hands and knuckles Fully adjustable frame Throat depth of 3-7/8 inches	
34	1	unit	Sprayer Paint / Spray Gun (600W) Rated Power 600W Amperage at Voltage 220V-230V 2.5A Flow Rate 1000ml/min. Max. Spraying Pressure 0.1-0.3 bar Max. Viscosity 100 DIN-s Nozzle Ø 2.5mm Reservoir Capacity 900mL Weight 2.9kg	

Item	Qty	Unit	Specification	Statement of Compliance
35	1	unit	SDS MAX Demolition Hammer with Variable Power Control Voltage 240 Volts Amperage 14 Amps Maximum Chuck Size 20 Millimeters Special Feature Variable-speed Product Dimensions 27.56"L x 10.24"W x 4.72"H Item Weight 1 Pound Item model number D25901K Wattage 1550 watts Tool Holder SDS MAX	
36	1	unit	Professional Rotary Hammer with SDS max Impact rate at rated speed 1,475 – 2,700 bpm Rated speed 165 – 300 rpm Rated input power 1500 W Impact energy (according to EPTA 05/2016) 12.5 J Weight 8.2 kg Tool holder SDS max Drilling dia. concrete, hammer drill bits 12 – 45 mm Opt. appl. range concrete, hammer drill bits 20 – 40 mm Drilling dia. concrete, breakthrough drill bits 80 – 80 mm Drilling diameter in concrete with core cutters 125 mm Max. drilling diameter in wood 80 mm	
37	1	unit	Professional Cordless Brushless Circular Saw 18V BITURBO with L-BOXX Saw blade diameter 190 mm No-load speed 2,500 – 5,000 rpm Saw blade bore diameter 30 mm Guide rail compatible yes Max. cutting capacity in wood (90°) 68mm Max. cutting capacity in wood (45°) 50mm	
38	3	pcs	Professional ProCORE18V 8.0Ah 18V Battery Battery voltage 18.0 V Weight 0.955 kg Battery dimensions (width x length x height) 77 x 117 x 69 mm	
39	2	unit	Brushless Cordless 4" Angle Grinder Voltage 20V Max Battery Cell Type Lithium-Ion Disc Diameter 100mm Spindle Thread M10 Switch Type Slider	

Item	Qty	Unit	Specification	Statement of Compliance
			No Load Speed 9,000 RPM Soft Start Yes E-clutch Yes E-brake Yes INCLUDES: 1 x Brushless Cordless 4" Angle Grinder 20V 2 x 5.0Ah Battery 1 x Charger 1 x Side Handle 1 x TSTAK Toolbox	
40	2	unit	Professional BITURBO Brushless Cordless Drill Driver 13mm, 18V (Heavy Duty) Torque (soft/hard/max.) 84/100/150 Nm No-load speed (1st gear / 2nd gear) 0 – 550 / 0 – 2,200 rpm Battery voltage 18.0 V Torque (max) 150 Nm Battery type Lithium-Ion Chuck capacity, min./max. 1.5 / 13 mm Weight excl. battery 2.1 kg Torque settings 25+1 INCLUDES: Starter Kit 18V 3.0Ah Li-Ion Battery and Multi-volt quick Charger	
II. ELECTRICAL SUPPLIES, TOOLS, AND EQUIPMENT				
1	5	pcs	Pliers 8" Made of forged alloy steel Meets or exceeds ASME standards, including load and cut tests Specially designed to cut copper Flat nose with teeth and pipe grip Hardened side cutting blade Comfortable non-slip PVC handles Ideal for cutting, twisting, straining, and gripping wires For general clamping and bending small rods and metal sheet	
2	5	pcs	Dyn grip Long Nose Pliers 8" Fixed joint design for bending, turning and cutting Long nose for use in tight spaces Meets ANSI specifications Drop-forged steel for strength and durability	
3	2	pcs	Side Cutter Combination Pliers 8" Heavy Duty, Rust resistant, Chrome Vanadium, VDE, Ergonomic grip Handle,	

Item	Qty	Unit	Specification	Statement of Compliance
			Soft grip Maximum Voltage 1000V	
4	3	unit	Aluminum Telescopic Ladder Foldable Ladder Double Side Compact Design Faster Operation Safety Lock Easy to Carry Strong Mechanism High Load Capacity Model HT-206: 2 x 6 steps (dual-sided for A-frame configuration) Max Load Capacity: 150 kg	
5	2	unit	Fiberglass A-Type Industrial Ladder Height: 12 ft USAOSHA / ANSI Standards Capable of supporting 225 lbs. to 300 lbs. Multi-functional tools slots for increased productivity Made of non-conductive fiberglass rails Pinch-resistant side braces and skid-resistant rubber feet Aluminum angle feet with heavy duty corrugated rubber thread	
6	50	pcs	Led Lite A50 Bulb E27 Base 6 Watts Daylight Up to 85% energy saving High color rendering index Mercury free SMD LED Technology Less heat emission CE and RoHS Compliant 20,000 hours of operation	
7	30	pcs	Led Bulb E27 5w SKU 147400005078 Application Indoor Finish Matte Material Polycarbonate aluminum Series Classic Series Unit of Measurement Pc Size 600x110mm Voltage 170-240V	
8	30	pcs	Addressable Smoke Detector AW-D101 Addressable-analog communication Low standby current for continuous monitoring ($\leq 2.5\text{mA}$) Two-wire connection Two LEDs (RED), blinks in normal condition and becomes stationary during fire Remote test from Panel	

Item	Qty	Unit	Specification	Statement of Compliance
9	50	pcs	LED Downlight 9W LED DL-RC-US R125 9W Extra Bright High system efficacy up to 85 lm/W Comfortable Light Light without flicker reduces stress while working/living underneath Energy Saving	
10	50	pcs	LED Downlight 16W LED ECO DOWNLIGHT LITE 3000K 16W LVD-DLE2-R-16W-AM (3000K)	
11	50	pcs	LED Downlight 6W LED DL-RC-US R125 6W 4000K	
12	2	unit	8 in 1 Wire Stripping Pliers Multifunction Material: Stainless Steel Plier head hardness: HAC55±2° Stripping: 1,1.5,2,2.5,4mm Cutting: 25mm ² Description: Multi-functional Design: This stainless steel wire stripper integrates multiple tools including cutting, stripping, slicing cables, dividing wires, winding, opening, and pulling cables, suitable for various electrical operations. High-quality Materials: Made of 3Cr13 stainless steel material, it has good hardness and corrosion resistance. The edge, with special heat up to HRC55±2° Strong Practicality: Suitable for stripping wires of AWG18-10/6,1.0,1.5,2.5,4.0mm ² and can cut cables up to 25mm ² .	
13	60	pcs	LED t8 Tube & Box Type Set (Single-ended) 18W Color Temperature: Daylight 6500K Life Hours: 15,000H Operating Voltage: 180-240V Beam Angle: 180° Lamp Base: G13 Color Rendering Index: CRI>80	
14	1	set	Digital AC Trur RMS 6000 count Digital Clamp Meter Multimeter Multi Tester Display: VA color display screen Measurement Type: TRUR RMS 6000 counts AC Current: 60A/600A/1000A DC Voltage: 600mV/6V/60V/600V/1000V AC Voltage: 600mV/6V/60V/600V/750V	

Item	Qty	Unit	Specification	Statement of Compliance
			Resistance: 600/6k/60k/600k/6M/60M Capacitance: 60.00nF/600.0nF/6.000uF/60.00uF/600.0uF/6.000mF/60.00mF Frequency: 10Hz/100Hz/1000Hz/10kHz/100kHz/1000kHz/10MHz Temperature: -40.0 ~1000.0 (-40.0~1832.0) Battery: 3pcs LR03 AAA batteries	
15	20	pcs	Led Slim Downlight Round 12 WATTS DAY LIGHT 6500K	
16	2	set	Digital Multimeter Multi Tester Model: DM310002 Display : TRUR RMS 6000 counts DC/AC Current: 6000uA/60mA/600mA/10A DC Voltage: 600mV/6V/60V/600V/1000V AC Voltage: 600mV/6V/60V/600V/750V Resistance: 600Ω/6kΩ/60kΩ/600kΩ/6MΩ/60MΩ Capacitance: 10nF/100nF/1000nF/10uF/1000uF/10mF/100mF Frequency: 10Hz/100Hz/1000Hz/10kHz/100kHz/1000kHz/10MHz Duty cycle: 1%~95% ±(2.0% +3) Non-contact voltage detection live line or neutral Line distinguish Diode test Max/Min and Data hold With backlight function With flash light function With lower battery indication function With input jack LED indicate With 3pcs x LR03 AAA batteries	
17	2	set	Digital Insulation Tester 4000 Megaohms Megger Resistance Tester Design compliant with IEC 61010-1 MΩ function with automatic live circuit detection (>30 Volts AC/DC) Short circuit current up to 2mA Continuity test with buzzer alarm Large 4200 counts display with log bar and backlight Auto Hold function Auto Range Auto discharge function Auto power save: Enables about 10 minutes after the last operation	

Item	Qty	Unit	Specification	Statement of Compliance
18	3	pcs	Panel Board Bolt on Type 4 Branches	
19	1	box	3.5mm² THHN/THWN Wire 12 AWG THHN Stranded Wire 3.50mm ² (#12 AWG) Approx. 150 meters	
20	1	box	2.0mm² THHN/THWN Wire 14 AWG THHN Stranded Wire 2.00mm ² (#14 AWG) Approx. 150 meters	
21	1	roll	PVC Flexible Hose ½ x 50 meters	
22	6	set	2 Gang Convenience Outlet 2 gang convenience outlet set	
23	5	set	2 gang switch with plate 2 gang switch with plate	
24	60	meter	14mm² THHN/THWN Wire 6 AWG Service drop per meter	
25	10	pcs	PVC Conduit Pipe 1" 1" diameter/ 3 meters length	
26	25	pcs	PVC Conduit Long Elbow 90 deg 1" diameter	
27	25	pcs	PVC Conduit Coupling 1" 1"	
28	20	pcs	PVC Female Adapter with Locknut 1" 1"	
29	20	pcs	PVC Male Adapter with Locknut 1" 1"	
30	20	pcs	PVC Conduit Pipe ¾" ¾" diameter/ 3 meters length	
31	20	pcs	PVC Conduit Long Elbow 90 deg ¾"	
32	20	pcs	PVC Conduit Coupling ¾" ¾"	
33	20	pcs	PVC Female Adapter with Locknut ¾" ¾"	
34	20	pcs	PVC Male Adapter with Locknut ¾" ¾"	
35	1	pcs	PVC Pipe Conduit Bender Spring Pipe Material: square line 75# steel ¾"	
36	1	pcs	Heavy duty EMT Pipe Bender 50-75mm Heavy Duty	
37	3	pcs	Circuit Breaker Bolt on 60 A Circuit Breaker 3P Bolt on 60 A	
38	3	pcs	Circuit Breaker 3P Bolt on 50A Circuit Breaker 3P Bolt on 50 A	
39	3	pcs	Circuit Breaker 3P Bolt on 20A Circuit Breaker 3P Bolt on 20 A	
40	3	pcs	Circuit Breaker 3P Bolt on 15A Circuit Breaker 3P Bolt on 15 A	

Item	Qty	Unit	Specification	Statement of Compliance
41	20	pc	Round Recessed Downlight 12W	
42	3	set	Switch Socket Cassette Screw 10 pcs/set Adjustment range 65-82mm	
43	2	unit	Soldering Iron Power: 100W Type: Industrial Electric Soldering Iron Industrial Quality: Designed for heavy-duty use and reliability.	
44	2	roll	Royal Cord/ Portable Cord 12/2C SJT 300 volts 75 meters/ roll	
45	3	pcs	Panel Box 6 holes	
46	30	pcs	Heavy duty extension outlet 4-gang Surface Type 15 amperes capacity / maximum 3,750 watts PVC and ABS material for heavy duty and protection finish	
47	3	pcs	Soldering Lead 50g 60/40.5mm w/ 2.2% flux rosin core	
48	15	pcs	Junction Box w/ cover fire retardant	
49	5	pcs	Square Box w/ cover Fire Retardant	
50	15	roll	PVC Insulating Tape / Electrical Tape PVC THPET1103 Length:9.15m(10yards) Color: Black Width:18mm Thickness:0.13mm	
51	15	pcs	Emergency light rechargeable lead acid battery Output voltage : 6V Capacity : 4.5AH	
52	30	pcs	Emergency light Twin Head Emergency Lamp 32-hour duration for one head 17-hour duration for two heads 24 x 0.06W LED 6V 4.5Ah Sealed Lead Acid Battery 230V 60Hz 24-hour charging time 3.5 in. dome reflector Built-in AC charger	

Item	Qty	Unit	Specification	Statement of Compliance
53	5	pcs	Manual Pull Station for Fire Alarm System 24V Conventional Type Surface mount design Power: 24V DC (normal voltage) Built-in 470-ohm trigger resistor RESETTABLE features Lock key for reset switch access Polarized	
54	2	pcs	Welding Electrode Holder High temperature, non-conducting Thick comfortable handle Non-slip design. High strength and hardness	
55	25	pcs	Traffic and Safety-First Plastic Cord / Cable Protector 2 Channels 100 x 25 x 4.5cm	
56	3	pcs	VDE High Leverage Diagonal Side Cutter Plier Rust resistance High Leverage Diagonal Side Cutter One-hand usage, soft grip Anti-slip shoulders, Ergonomic grip handle Hardened cutting edges Material: Chrome Vanadium Maximum voltage: 1,000 V VDE Tensile strength ordinary steel wire: 1,600 N/mm ²	
57	2	pcs	Fiberglass Wire Conductive Electrical Cable Puller 30m Fiberglass Fish Tape Reel with Impact Case	
58	100	pcs	E27 5W Candle Light Daylight Watts: 5W Operating Voltage: 230V AC 50/60Hz Lumens: 500 Lumens Lifehours: 15,000 Beam Angle: 280° CRI: ≥80 Energy Savings: 85%	
59	50	pcs	LED Bulb Daylight Wattage: 10W Cap: E27 Color Temperature: Daylight Lumen: 1400 Voltage: 100-240V Dimension: 67 x 120mm Life hours: 30000	

Item	Qty	Unit	Specification	Statement of Compliance
60	100	pcs	LED Bulb Daylight Wattage Lumens: 1530 Life hours: 15,000 Operating Voltage: 230V AC 50/60Hz Energy Savings: 50% CRI: ≥ 80	
61	6	box/carton	T8 LED Tube Wattage: 18W Luminous Flux: 1800lm Color Temperature: 6500K(Daylight) Beam Angle: 200° Degrees Wiring: T8 Double Ended Material: Plastic Voltage: 170V – 240V CRI : ≥ 80 Lifespan: 15,000hrs 30 pcs/ box	
III. OTHER SUPPLIES, TOOLS, AND EQUIPMENT				
1	5	unit	Metal Locker Cabinet Double Security Locks Ventilation Holes Name Card Holder Orientation: 6 Shelves and 6 Hangers Color: Beige Dimension: L35.5" x W16" x H73" Thickness: 0.9mm	
2	9	pcs	Full Body Harness Heavy Duty Belt Set Belt: 45mm X1.33m Nylon Belt Webbing: 45mmx 1.69m Nylon Webbing Complies to CE and ANSI approved standards Meets EN 361/EN 358/EN 362/EN 12275/EN 354/EN 355 Standards	
3	12	unit	Working Jacket w/ Reflective Material: 80% Polyester + 20% Cotton Two chest pockets with flaps Two pen holders on chest Two deep front patch pockets Elasticated cuffs Adjustable hem with two buttons positions each side Piping detail to front and back incorporating scotchlite reflective materials Full front zip fastening with three hook and loop positions With vents Special pockets for building accessories, for instance screws	

Item	Qty	Unit	Specification	Statement of Compliance
			Packing: PVC bag with color paper Sizes: 4 LARGE, 4 X	
4	12	pcs	Working Trousers w/ Oxford Fabric Material: 80% Polyester + 20% Cotton Reinforcements with Oxford fabric on knees durable Triple seam in spots prone to tearing reflective piece around the chest to improve user's safety Can be used with knee foam pads Zipper closure type Two front pockets, each has a extra wide front patch pockets Two wide lined back pockets with flaps One side pocket with flap One hammer loop Knee pad pockets Slim Fit Packing: PVC bag with color paper	
5	120	pcs	Safety Gloves /Working Gloves Safety Gloves /Working Gloves Enhanced Grip: PVC dots provide a better grip for handling items. Comfortable Fit: Knitted cotton material offers breathability and comfort for extended wear. Durable Design: Made to withstand wear and tear in various working environments. HGVK05	
6	15	pcs	Rain Boots 100% Waterproof Protection: Seamless construction ensures full waterproofing, keeping your feet dry in wet environments. Lightweight Design: Crafted for comfort, the plain-toe design minimizes fatigue during extended work hours. Non-Slip Soles: Provide superior traction and stability on diverse surfaces, making them ideal for concrete construction and agricultural food processing tasks. Kick-Off Lugs: Simplify removal	
7	14	pcs	Rain Coat Gender Unisex Size range M → 2XL Workwear color Navy Blue Seams Waterproof Support material details Canvas - 100% polyester - PVC coating Aeration place Back Hood type Fixed hood Fastening Zipper Closure	

Item	Qty	Unit	Specification	Statement of Compliance
			Adjustable Cuffs By snap fastener Inner wrist Elastic Waist Elasticated waist Lower body Bottom drawstring Tightening trouser bottoms Snap fastener Top Reflective Tape Chest (2 bands) Bottom Reflective Tape Pant (2 band) Number of exterior pockets 4 Outer Pockets 2 Flap Pockets, 2 Hand Pockets Marking type Screen printing, Transfer printing Elastic Waist SIZES: 2 - MEDIUM 4 - LARGE 4 - XL	
8	2	pcs	Auto Darkening Welding Helmet (CAXW-MA1) Seamless Continuous Control Sensitivity Adjustment: Power Supply (Solar) Delivered Power (3.7V Li-Ion): Equipped with a reliable 3.7V Li-Ion battery for stable power delivery and enhanced performance. Light Shade (DIN4): Dark Shade (DIN9~DIN13): Automatically adjusts to provide optimal eye protection from the welding arc, with a range of dark shades (DIN9 to DIN13) based on the welding process. Switching Time ($\leq 3 / 10,000$ s): Features a fast switching time of less than 3/10,000 seconds	
9	10	pcs	Reflection Safety Vest with Common Reflective Strip Fluorescent Color: Fluorescent yellow Common reflective strip + Conforms to EN471 class 2 Front zipper for easy opening and closing Two 17.5cm*17.5cm pockets to hold keys for cellphones or other small items Eye-catching color matching and color contrast edge more eye-catching	
10	4	pcs	Industrial 11 inches C-Clamp Locking Plier Material: Carbon steel Size: 11 inches Hardness: HRC40-HRC50 Weight: 790g	

Item	Qty	Unit	Specification	Statement of Compliance
			Construction: Drop-forged, tempered steel Finish: Nickel plated	
11	10	bundle	100 pcs cable ties Size: 4.8 x 300mm Material: Nylon 66 Color: White	
12	2	pcs	100 cm Spirit Level Industrial Type: Industrial Spirit Level Bar Length: 100cm Width: 5.3cm Height: 3.4cm Material: Aluminum (1.5mm thick) Accuracy: 0.5mm/m Milling: Double Sided	
13	2	pcs	10cm Mini Magnetized Hand Level Material: Acrylic Vial Length: 10 cm Magnetized for easy attachment to metal surfaces UV resistant for durability in various conditions Heavy-duty construction ensures long-lasting performance Shockproof end caps protect against impact damage Thickness: 1.5 mm for enhanced strength Complies with VPA standards for quality assurance	
14	2	set	16V/M16 Lithium-Ion Cordless 3D Laser Level Green Laser Level Range: 0-35m Model: HLL301201 Green laser level Rated Voltage: 16V Working range: 0~35m Self-levelling angle: ≤4° Laser class II, <1mW With 1pcs 360° horizontal and 2pcs 360° vertical laser line Operating temperature: 0~+40°C Storage temperature: -10~+50°C Include: 1pc x Magnetic liftable rotating stand 1pc x Rotary base with 3 adjustable feet 1pc x Laser target plate 1pc x Glasses 1pc x Remote control 1pc x 2.0Ah battery pack (FBLI1620) 1pc x Charger (FCLI1613) Charge volts: 220-240V~50/60Hz	

Item	Qty	Unit	Specification	Statement of Compliance
15	1	set	High Pressure Washer 1800 Watts Model: HPWR18008P Specifications Power: 1800W Motor: Carbon brush Input Power: 1800W Max Pressure: 150 Bar (2200 PSI) Flow Rate: 6.0L/min Voltage: 220-240V ~ 50/60Hz Product Dimensions: 30cm x 22cm x 81cm (L x W x H) Product Weight: 7kg Accessories Included: >1 set water spray gun >5m high-pressure hose >1 pc soap bottle >195mm Pressure Washer Pool Hi-Vac Suction Sweeper Brush >fix brush 420 x 130mm suitable for high pressure washer	
IV. PLUMBING SUPPLIES, TOOLS, AND EQUIPMENT				
1	20	pcs	Gooseneck Faucet Stainless 304 Wall Mount Lever Type	
2	20	pcs	Heavy Duty Bidet Spray Set Material: Made from 304 stainless steel, which is corrosion-resistant and environmentally friendly. Nozzle: Equipped with a brass adjustable nozzle for precise control. Hose: Comes with a 1.5m 304 stainless steel hose for flexibility and durability ¹² . Easy Installation: Designed for straightforward installation in your bathroom.	
3	20	set	Water Tank Fittings for Toilet Flush Push Button Type	
4	20	pcs	Gooseneck Faucet Stainless 304 Sink Mount Lever Type	
5	10	pcs	Wall Mounted Faucet Lever Type with bibb (6")	
6	10	pcs	Wall Mounted Faucet Lever Type Stainless 304 1/2" x 2" Modern Design	
7	6	unit	Water Heater Rated Power: 4.5 kW Power Supply: 230 V, 60 Hz	

Item	Qty	Unit	Specification	Statement of Compliance
			Protects against fire & electrical hazards with 9 safety features Protects against bacteria with Ag+ Crystal Material	
8	20	pcs	PPR Ball Valve PPR ball valve 1/2"	
9	30	pcs	Brass Ball Valve 1/2" brass	
10	2	set	Faucet and Sink Installer For common faucet installations and sink strainers. Unique cubed insert provides a variety of common nut sizes. Ideal for most common 2-, 3-, 4-, and 6-tab mounting nuts. Wrench for tight shut-off valves. Retainer for 3 or 4 slot strainer baskets.	
11	35	pcs	Hose Bibb Faucet 100% brass body and center cartridge Ceramic disc fitting for quarter turn quick open faucet Easy installation and maintenance	
12	25	pcs	Flexible Inlet Hose with spanner Stainless 304 1/2 x 1/2 14"	
13	25	pcs	Flexible Inlet Hose with spanner Stainless 304 1/2 x 1/2 16"	
14	25	pcs	Flexible Inlet Hose with spanner Stainless 304 1/2 x 1/2 20"	
15	1	set	PVC PPR Pipe Fusion Welding Machine Voltage:220V-240V~50/60Hz Input power: 800W/1500W Thermoregulator:0 - 300°C Includes: With heating sockets 20、25、32、40、50、63mm With 1pc measuring tape With 1pc pipe cutter With 1pc hex key With 1pc screwdriver	
16	1	set	P20S/20V 6 Pcs Combo Kit with Lithium-Ion Heat Gun Model: COSLI250801 Rated Voltage: 20V With 1pc x Lithium-ion heat gun (HGLI20025) With 1pc x Heat gun (HG200058)	

Item	Qty	Unit	Specification	Statement of Compliance
			Lithium-ion heat gun (HGLI20025) Temperature: 300/550°C Airflow: 100/200 L/min Heat gun(HG200058) Rated Voltage: 220V-240V~50/60Hz Input power: 2000W Temperature: 50/50-600/50-600°C Airflow: 450/300/450 L/min Adjustable temperature with LCD display for precise control Includes: 2pcs x Reduction nozzle 2pcs x Reflector nozzle 2pcs x Flat nozzle 1pc x Scraper 1pc x Snap-off blade knife(HKNS11805) 1pc x Putty trowel(PUT08040) 1pc x Screw driver(HSDSSL5100) 1pc x Package of heat shrink tubing 2pcs x 5.0Ah battery pack(FBLI20031) 1pc x 20V charger(FCLI2001) Charge volts: 220-240V~50/60Hz Packed by carrying case with WARRANTY CARD	
17	1	unit	1.5Hp Submersible Sewage Water Pump Voltage: 220V-240V ~ 60Hz Input Power: 1000W Max. Head: 16m Max. Flow Rate: 216.7L/min Max. Depth: 7m Piping Diameter: 2" Cable Length: 10m	
18	1	roll	2-inches Discharge Duct Hose 20-meters (65.6 ft.) for Submersible / Water Pump 2 inches diameter	
19	70	pcs	PPR Elbow 90°, 1/2" PPR Elbow 90°, 1/2"	
20	60	pcs	PPR Elbow 90°, 3/4" PPR Elbow 90°, 3/4"	
21	60	pcs	PPR Coupling 1/2" PPR Coupling 1/2"	
22	60	pcs	PPR Coupling 3/4" PPR Coupling 3/4"	
23	50	pcs	PPR Equal Tee 1/2" PPR Equal Tee 1/2"	
24	50	pcs	PPR Equal Tee 3/4" PPR Equal Tee 3/4"	
25	150	pcs	PPR Clip ½" PPR Clip for ½"	
26	150	pcs	PPR Clip 3/4 " PPR Clip 3/4 "	

Item	Qty	Unit	Specification	Statement of Compliance
27	30	pcs	PPR PIPE PN-20 ½ " 1/2" AT 4M LENGTH	
28	20	pcs	PPR PIPE PN-20 ¾ " 3/4" AT 4M LENGTH	
29	35	pcs	Lavatory Faucet Stainless 304 Sink Mount Lever Type	
30	15	set	Marine Epoxy Non-Sag 1 Liter per set Heavy-duty epoxy adhesive Non-sag up to 1/2 inch thick For vertical or horizontal applications Adheres to either damp or dry surface 100% solids content Solvent-free formulation Low VOC Non-shrinkable Water-resistant Solvent-resistant Chemical-resistant Sandable and Paintable	
31	5	gallon	Water-Based Polyurethane Membrane 1 Gallon-Gray Thick pasty liquid, single pack, easy to use Excellent curing UV resistant, superb elongation, excellent in tensile Anti-fracture, no blistering No reinforcement required No tar, no bitumen, non-toxic Ideal for waterproofing of concrete roofs For internal and external use For concrete canopy	
32	7	gallon	Rapid setting plugging mortar Gallon Rapid-setting, stopping leaks instantly Easy to Use – just add water Durable – provides sufficient strength Chloride-free – doesn't cause corrosion Sealing of corner joints Stopping leaks Repairing water-retaining structures Filling holes before waterproofing Creating coving on swimming pools	
33	5	gallon	Negative Side Flexible Cementitious Waterproofing Flexible and durable Excellent adhesion to most substrates Excellent waterproofing of the negative side Able to withstand high hydrostatic	

Item	Qty	Unit	Specification	Statement of Compliance
			pressure Bridge hairline cracks Non-toxic Can be applied to damp surfaces Negative side of above-ground walls Negative side of mid-rise houses/buildings Negative side of high-rise building walls Negative side of walls that are hard to waterproof outside	
34	20	roll	PTFE Tape 1/2in. x 10m PTFE material High quality 1/2in. x 10m	
35	1	Unit	Heavy Duty Wet and Dry Vacuum Cleaner Max. input power 1,250 W, Weight 9 kg, Container volume, net 21 l Dust class of wet/dry extractor L Rated input power 1,250 W Container volume, gross 25 l Container volume, net, water 15 l Dust bag volume, net 20 l Dust class L Filter surface area 2,300 cm ² Max. airflow rate (turbine) 65 l/s Max. vacuum pressure (turbine) 200 mbar Wheels, number 4	
36	1	Unit	Heat Gun Continuous Rating Input 1,600W Air Temperature (°C) Stage 1: 350 / 300 Stage 2: 500 / 500 Dimensions (L x W x H) 233 x 80 x 208 mm (9-1/8 x 3-1/8 x 8-3/16") Net weight 0.56 kg (1.2 lbs) Power supply cord 2.0 m (6.6 ft)	
37	1	Unit	Electric Leaf Blower, Vacuum, and Shredding Leaves Motor power 1,600 - 3,000 W Variable airflow speed 165 - 285 km/h Volume flow rate 576 m ³ /h Collection bag 50 l Reduction of leaf quantity 12:1 Tool dimensions (L x W x H) 670 x 230 x 1150 mm Weight (garden vac) 4.7 kg Weight (leaf blower) 3.4 kg Vibration emission value (ah) 2.5 m/s ² Uncertainty (K) 1.5 m/s ²	
38	11	pair	Safety Shoes Shoe type High shoe	

Item	Qty	Unit	Specification	Statement of Compliance
			Outsole material PU, 2d Anti-perforation insert Metal free Upper material Buffalo leather Upper finition material Smooth, Water repellent Safety toe-cap Composite Lining material Textile, Polyester Footbed material EVA, Polyamide Footbed characteristic Removable, Breathable, Pre-molded Outsole finition Injected Weight (g per shoe) 720 Size range 39 → 48 Size Range: 1 pair size 40(EU) 4 pairs size 41(EU) 4 pairs size 42(EU) 2 pairs size 43(EU)	
39	2	pcs	Four-Sided Warning Cone (Wet Floor) 4-Sided Visibility Moulded plastic prevents cracks and chipping, even outdoors. The wide base adds stability Cones stack for easy storage. Includes holes at the top to attach chains, tape or signage.	
40	2	pcs	Four-Sided Warning Cone (No Parking) 4-Sided Visibility: Moulded plastic prevents cracks and chipping, even outdoors. The wide base adds stability. Cones stack for easy storage. Includes holes at the top to attach chains, tape or signage.	
41	2	pcs	Four-Sided Warning Cone (Closed/No Entry) 4-Sided Visibility: Moulded plastic prevents cracks and chipping, even outdoors. The wide base adds stability. Cones stack for easy storage. Includes holes at the top to attach chains, tape or signage.	
42	2	pcs	Floor Signage (Repair/Work in progress) 4-Sided Visibility Moulded plastic prevents cracks and chipping, even outdoors. The wide base adds stability. Cones stack for easy storage. Includes holes at the top to attach chains, tape or signage.	

Item	Qty	Unit	Specification	Statement of Compliance
V. THREADED PPR ACCESSORIES				
1	45	pcs	PPR Male Adapter 20 x 1/2" Threaded Size - 20 x 1/2"	
2	45	pcs	PPR Female Adapter 20 x 1/2" Threaded Size - 20 x 1/2"	
3	40	pcs	PPR Female Tee 20 x 1/2" Threaded Size - 20 x 1/2"	
4	40	pcs	PPR Male Tee 20 x 1/2" Threaded Size - 20 x 1/2"	
5	40	pcs	PPR Female Elbow 20 x 1/2" Threaded Size - 20 x 1/2"	
6	40	pcs	PPR Male Adapter 20 x 3/4" Threaded Size - 20 x 3/4"	
7	40	pcs	PPR Female Adapter 20 x 3/4" Threaded Size: 20 x 3/4"	
8	40	pcs	PPR Female Tee 20 x 3/4" Threaded Size: 20 x 3/4"	
9	20	pcs	PPR Female Elbow 20 x 3/4" Threaded 20 x 3/4"	
10	40	pcs	PPR Male Tee 20 x 3/4" Threaded Size - 20 x 3/4"	
VI. STRUCTURAL/CIVIL WORKS				
1	8	pcs	G.I. PIPE 4 inches diameter Schedule 40 Welded	
2	4	pcs	Checkered Metal Plate Material: High-quality steel with a checkered pattern for added grip Sizes: 4ft x 8ft with 3.0mm thickness	
3	50	pcs	Angle Bar Size - 2" x 2" Thickness - 4.5mm	
4	3	pcs	Stainless Steel Perforated Sheet 4 ft x 8 ft 0.5mm	
5	26	linear meter	GI Wall Cladding Nominal thickness 0.4mm Rib height 10mm Material Hot dip Metallic coated steel	

Item	Qty	Unit	Specification	Statement of Compliance
VII. ROOFING WORKS				
1	10	pcs	G.I. TUBULAR 2 X 6 SIZE - 2 X 6 TUBULAR GI THICKNESS 2.00 mm	
2	20	pcs	C- PURLINS 2 X 4 SIZE - 2 X 4 THICKNESS - 1.5 mm	
3	65	pcs	SAGROD 550mmx12mm dia. Plain Bar w/ standard nuts & washers	
4	10	pcs	SUB FASCIA 2 X 6 C-PURLINS 1.5 MM	
5	5	pcs	FASCIA BOARD Standard Thickness: ~12mm Width: 12" Length: 12ft Color: Cement Gray	
6	50	square meter	PRE-PAINTED METAL ROOFING SHEET GA 26 GA 26 LONG SPAN 0.6MM	
7	8	pcs	Pre-painted Box Gutter, GA 24 0.61 MM X 2.44 M	
8	15	pcs	Pre-painted Box End Flashing, GA 24 0.61 MM X 2.44 M	
9	1	roll	PE Foam Insulation 50m Double Foil 10mm	
10	15	pcs	Pre-painted Wall Flashing, GA 24 GA 24	
VIII. OTHER ITEMS				
1	5	pack	Welding Rod 2.5MM N-6013 5 kg per pack	
2	2	box/carton	Tek screw 2" Metal Tek screw	
3	5	box/carton	Cutting Disc Cutting Disc 4"	
4	15	pcs	Grinding Disc 4"	
5	1	set	Steel Door Panel: 900mm Width x 2.1mtr Height Galvanized Iron Gauge 18 44mm. Thick w/ Paper Honeycomb Insulation Glass: 400mmx750mmx6mm Clear Jamb: 2"x4" Single Rabbet Galvanized Iron Gauge 16 Lockset: None Painted: Epoxy Primer Gray	

Item	Qty	Unit	Specification	Statement of Compliance
			Hinges: 4 Pcs Stainless Steel Flag Hinges Door handling: RHA	
6	2	set	Doorknob Lever type Heavy Duty	
7	5	box/carton	Blind Rivets 5/32 x 1"	
8	2	pcs	Hand Riveter Applicable rivet size:2.4mm, 3.2mm,4mm,4.8mm	
9	3	pcs	Steel Brush (Plastic Handle) Straight Type Durable, Heavy Duty	
10	2	pcs	Aviation Snip Bulldog Cuts straight, left, and right directions. Chrome-molybdenum alloy steel forged blades for strength and durability Serrated edges for stable bite and prevents slipping Center fastener for high tensile strength and provided for longer life non-slip dual material handle for comfort grip	

NOTES:

For the purpose of bid evaluation, the required evidence as reference to the statement of compliance shall be in the form of brand and/or technical specifications of the offered item.

Example:

Specification	Statement of Compliance
Angle Bar Size - 2" x 2" Thickness - 4.5mm	Comply, brand x, photo or brochure of the offered item